

DK-84461-M1-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Harmony Safety Module XPSU and XPSB

SCHNEIDER ELECTRIC AUTOMATION GMBH SCHNEIDERPLATZ 1 MARKTHEIDENFELD 97828 **GERMANY**

SCHNEIDER ELECTRIC AUTOMATION GMBH SCHNEIDERPLATZ 1 MARKTHEIDENFELD 97828 **GERMANY**

PT. Schneider Electric Manufacturing Batam JL Beringin Lot 208, 16A BIP Muka Kuning Kel. Muka kuning Kec., Sungai Beduk, Batam, 29433, Indonesia

☐ Additional Information on page 2

See Page 2



XPSUAB*1C**, XPSUAF*3A**, XPSUAK*2A**, XPSUS*2A**, XPSUAT*3A3A*

The report was revised to include technical modifications.

☑ Additional Information on page 2

IEC 60947-5-1:2016. IEC 60947-1:2007.

IEC 60947-1:2007/AMD1:2010, IEC 60947-1:2007/AMD2:2014

4789614749 issued on 2021-04-14

This CB Test Certificate is issued by the National Certification Body



□ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
 ☑ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
 □ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
 □ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-05-19

Original Issue Date: 2019-06-11

Signature:

Jan-Erik Storgaard



DK-84461-M1-UL

Additional Model(s):

Series: XPSUAB*1C**, XPSUAF*3A**, XPSUAK*2A**, XPSUS*2A**, XPSUAT*3A3A**, XPSUDN*3A**, XPSUEP*4A**, XPSUVN*1A**, XPSBAT12A1A**, XPSBAC*4A**,

- = Power Supply:
 - 1 = 24 Vac/Vdc.
 - 3 = 48 240 Vac/Vdc.
- ** = Terminal Type:
 - C = Pluggable connector with cage clamp (Screwless Terminal)
 - P = Pluggable connector with screw clamp (Screw Terminal)

See test report for Nomenclature

Ratings:

Power Supply:

- 24 V ac/dc
- 48-240 V ac/dc Outputs:

Outputs:

- AC-15: 250 Vac, NO 3 A, NC 1 A
- DC-13 : 24 Vdc, NO 3 A, NC 1 A

(Except XPSUAB*1C**: DC-13: 24 Vdc, NO 2 A, NC 1 A)

IP40 for housing

IP 20 for terminals.

Summary of Modifications:

The original report was modified to include the following changes:

Add new models, add new relay;

Test item particulars and standard information have been revised;

Model designation was revised.

Additional information (if necessary)



- □ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☑ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
 ☐ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- □ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-05-19

Original Issue Date: 2019-06-11

Signature:

Jan-Erik Storgaard

for but Superial