# **GVAN11**

TeSys Deca Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, side mount, screw clamp





# Main

Main		
Range	TeSys TeSys Deca	
Device short name	GVAN	
Product or Component Type	Auxiliary contact block	
Product Compatibility	GV2ME GV2RT GV2L GV3P GV3L GV2LE GV2LE	
Mounting Location	Left side	
Pole contact composition	1 NO + 1 NC	

#### Complementary

24240 V DC     [Ith] conventional free air thermal current	[Ui] rated insulation voltage	600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14
Protection type   GB2CB circuit breaker   GG fuse 10 A	[Ue] rated operational voltage	
Mechanical durability	[Ith] conventional free air thermal current	6 A
Minimum switching current         5 mA           Minimum switching voltage         17 V           Rated operational power in VA         300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles	Protection type	
Minimum switching voltage	Mechanical durability	100000 cycles
Rated operational power in VA  300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 850 VA 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V D	Minimum switching current	5 mA
## 414 VA 690 V AC-15 100000 cycles ## 500 VA 110127 V AC-15 100000 cycles ## 500 VA 110127 V AC-15 100000 cycles ## 500 VA 400 V AC-15 100000 cycles ## 650 VA 440 V AC-15 100000 cycles ## 720 VA 230240 V AC-15 100000 cycles ## 850 VA 380415 V AC-15 100000 cycles ## 850 VA 380 V AC-15 100000 cycles	Minimum switching voltage	17 V
140 W 110 V DC-13 100000 cycles         140 W 24 V DC-13 100000 cycles         180 W 60 V DC-13 100000 cycles         240 W 48 V DC-13 100000 cycles         Tightening torque       12.39 lbf.in (1.4 N.m) screw clamp terminals         Height       3.50 in (89 mm)         Width       0.37 in (9.3 mm)         Depth       2.60 in (66 mm)         Net Weight       0.11 lb(US) (0.05 kg)	Rated operational power in VA	414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles
Height       3.50 in (89 mm)         Width       0.37 in (9.3 mm)         Depth       2.60 in (66 mm)         Net Weight       0.11 lb(US) (0.05 kg)	Rated operational power in W	140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles
Width       0.37 in (9.3 mm)         Depth       2.60 in (66 mm)         Net Weight       0.11 lb(US) (0.05 kg)	Tightening torque	12.39 lbf.in (1.4 N.m) screw clamp terminals
Depth       2.60 in (66 mm)         Net Weight       0.11 lb(US) (0.05 kg)	Height	3.50 in (89 mm)
Net Weight 0.11 lb(US) (0.05 kg)	Width	0.37 in (9.3 mm)
· // 3/	Depth	2.60 in (66 mm)
Color Dark grey	Net Weight	0.11 lb(US) (0.05 kg)
	Color	Dark grey

#### Environment

Environmental characteristic	Normal environment
Product Certifications	UKCA

# Ordering and shipping details

Category	22367-MANUAL STR PROTECTOR - GV2
Discount Schedule	l11
GTIN	3389110343489
Returnability	Yes
Country of origin	CZ

### Packing Units

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.59 in (1.500 cm)
Package 1 Width	2.76 in (7.000 cm)
Package 1 Length	3.54 in (9.000 cm)
Package 1 Weight	1.62 oz (46.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.74 in (9.500 cm)
Package 2 Width	3.94 in (10.000 cm)
Package 2 Length	5.98 in (15.200 cm)
Package 2 Weight	17.99 oz (510.000 g)
Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Height	5.91 in (15.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	7.26 lb(US) (3.294 kg)

### Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Yes
Compliant EPEU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
₫Yes
Product Environmental Profile
☑ End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Contractual warranty

Warranty	18	months

GVAN11