


NSYTRR26T

Terminal block, Linergy TR, spring type, feed through, 3 levels connected, 6 points, 2.5mm², grey, set of 50



Main

| | |
|------------------------------------|---|
| Range | Linergy |
| Product name | Linergy TR |
| Product or Component Type | Terminal block |
| Device short name | TRR |
| Accessory / separate part category | Connection accessory |
| Terminal block type | Passthrough |
| Terminal block level | 3 |
| Mounting Mode | Clip-on |
| Nominal cross section | 0.00 in ² (2.5 mm ²) |
| Length | 3.92 in (99.5 mm) |
| Color | Gray |
| Quantity per Set | Set of 50 |

Complementary

| | |
|--------------------------------|---|
| Width | 0.20 in (5.2 mm) |
| Height | 2.28 in (58 mm) |
| Connections - terminals | 1 x spring terminal upstream 1 x spring terminal downstream |
| Number of connections | 2 |
| Connection position | Top |
| Number of measurement input | 3 |
| Cable cross section | 0.00...0.00 In ² (0.08...2.5 mm ²), flexible without cable end 0.00...0.01 In ² (0.08...4 mm ²), solid with cable end 0.00...0.00 In ² (0.2...2.5 mm ²), flexible with cable end 0.00...0.01 in ² (0.08...4 mm ²), solid without cable end |
| Wire stripping length | 0.39 in (10 mm) |
| Tool type | Connection flat screwdriver Disconnection flat screwdriver |
| [Ue] rated operational voltage | 500 V EN/IEC 60947-7-1 300 V CSA 600 V cURus |
| Line Rated Current | 20 A CSA 20 A EN/IEC 60947-7-1 20 A cURus |
| Material | Polyamide 6/6 insulating case Copper alloy connector and screw Copper alloy commoning link Chromium-nickel steel spring |
| Dielectric loss | 0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4 |
| Dielectric constant | 3.7 at 1 MHz |
| Resistivity | 10000 MΩ.M IEC 60093 10000 MΩ.m VDE 0303-T30 |
| Surface resistance | 1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30 |
| Creep resistance | 500 CTI (> 400 kV) IEC 60093 500 CTI (> 400 kV) VDE 0303-T30 |
| Flame retardance | V0 0.03 in (0.8 mm) UL 94 |

| | |
|-----------------------|--|
| Net Weight | 0.63 oz (18 g) |
| Range compatibility | Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys |
| Product Compatibility | Spacial enclosures |

Environment

| | |
|---------------------------------------|---|
| Product Certifications | EAC LR GL VDE CSA cURus |
| Dielectric strength | 1000 V IEC 60243-1 |
| Ambient air temperature for operation | -40...266 °F (-40...130 °C) IEC 60216-1 -40...266 °F (-40...130 °C) VDE 0304-T21 |




Ordering and shipping details

| | |
|-------------------|---|
| Category | 21715-IEC TERMINAL BLOCKS-NSY,AM1,DF6,GK1 |
| Discount Schedule | CP5 |
| GTIN | 3606480532658 |
| Returnability | No |
| Country of origin | PL |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.36 in (6 cm) |
| Package 1 Width | 4.53 in (11.5 cm) |
| Package 1 Length | 12.20 in (31 cm) |
| Package 1 Weight | 0.63 oz (18 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 50 |
| Package 2 Height | 2.36 in (6 cm) |
| Package 2 Width | 4.53 in (11.5 cm) |
| Package 2 Length | 12.20 in (31 cm) |
| Package 2 Weight | 32.38 oz (918 g) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 400 |
| Package 3 Height | 11.81 in (30 cm) |
| Package 3 Width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |
| Package 3 Weight | 17.39 lb(US) (7.889 kg) |

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |

| | |
|-----------------------------|---|
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|