

# LTMR08MFM

Motor controller, TeSys T, Motor Management, Modbus, 6 logic inputs, 3 relay logic outputs, 0.4 to 8A, 100 to 240VAC



## Main

Range	TeSys
Product name	TeSys T
Device short name	LTMR
Product or Component Type	Motor controller
Device Application	Equipment monitoring and control
Measurement current	0.4...8 A
[Us] rated supply voltage	100...240 V AC 50/60 Hz
Current Consumption	8...62.8 mA
Supply voltage limits	93.5...264 V AC
Communication Port Protocol	Modbus
Bus type	Modbus 2-wire RS 485 1...247 1.2...19.2 kbit/s, RJ45 2 shielded twisted pairs Modbus 2-wire RS 485 1...247 1.2...19.2 kbit/s, terminal block 2 shielded twisted pairs

## Complementary

[Ui] rated insulation voltage	690 V EN/IEC 60947-1 690 V CSA C22.2 No 14 690 V UL 508
[Uimp] rated impulse withstand voltage	4 KV supply, inputs and outputs EN/IEC 60947-4-1 6 KV current or voltage measurement circuit EN/IEC 60947-4-1 0.8 kV communication circuit EN/IEC 60947-4-1
Short-circuit withstand	100 kA EN/IEC 60947-4-1
Associated fuse rating	4 A gG output 0.5 A gG control circuit
Protection Type	Reverse polarity protection Locked rotor Earth-leakage protection Thermal overload protection Phase failure Overload Thermal protection Power factor variation Load fluctuation Phase unbalance Overload (long time)
Network and machine diagnosis type	Event recording Fault recording Waiting time after overload tripping Running hours counter/operating time Phase fault and earth fault trip counters Trip context information Starting current and time Motor control command recording Remaining operating time before overload tripping Trip history information
Logic input number	6
Input current	3.1 MA 100 V 7.5 mA 240 V
Current state 0 guaranteed	Logic input 0...40 V <= 15 mA 25 ms
Current state 1 guaranteed	Logic input 79...264 V >= 2 mA 25 ms

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Maximum output switching frequency	2 Hz
Load current	5 A 250 V AC logic output 5 A 30 V DC logic output
Permissible power	480 VA AC-15), I <sub>e</sub> = 2 A, 500000 cycles output) 30 W DC-13), I <sub>e</sub> = 1.25 A, 500000 cycles output)
Maximum operating rate	1800 cyc/h
Contacts type and composition	1 NO + 1 NC fault signal 3 NO
Metering type	Average current I <sub>avg</sub> Temperature Earth-fault current Imbalance current Phase current I <sub>1</sub> , I <sub>2</sub> , I <sub>3</sub> RMS
Measurement accuracy	5...15 % earth fault current internal measurement 1 % voltage 100...830 V) 3 % power factor 5 % earth fault current external measurement +/- 30 min/year internal clock 0,02 Temperature 1 % current 5 % active and reactive power
Overvoltage category	III
Connection pitch	0.20 in (5.08 mm)
Connections - terminals	Control circuit connector 1 0.00...0.00 in <sup>2</sup> (0.25...2.5 mm <sup>2</sup> ) AWG 24...AWG 14)flexible with cable end Control circuit connector 1 0.00...0.00 in <sup>2</sup> (0.2...2.5 mm <sup>2</sup> ) AWG 24...AWG 14)flexible without cable end Control circuit connector 1 0.00...0.00 in <sup>2</sup> (0.25...2.5 mm <sup>2</sup> ) AWG 24...AWG 14)flexible without cable end Control circuit connector 1 0.00...0.00 in <sup>2</sup> (0.2...2.5 mm <sup>2</sup> ) AWG 24...AWG 14)solid without cable end Control circuit connector 2 0.00...0.00 in <sup>2</sup> (0.2...1 mm <sup>2</sup> ) AWG 24...AWG 14)flexible with cable end Control circuit connector 2 0.00...0.00 in <sup>2</sup> (0.2...1.5 mm <sup>2</sup> ) AWG 24...AWG 14)flexible without cable end Control circuit connector 2 0.00...0.00 in <sup>2</sup> (0.5...1.5 mm <sup>2</sup> ) AWG 24...AWG 14)flexible without cable end Control circuit connector 2 0.00...0.00 in <sup>2</sup> (0.2...1 mm <sup>2</sup> ) AWG 24...AWG 14)solid without cable end
Tightening torque	Control circuit 4.43...5.31 lbf.in (0.5...0.6 N.m) flat 0.12 in (3 mm)
Pollution degree	3
Electromagnetic compatibility	Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4 Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC 61000-4-11 Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6 Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5 Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5 Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC 61000-4-5 Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC 61000-4-5 Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
Width	3.58 in (91 mm)
Height	2.40 in (61 mm)
Depth	4.82 in (122.5 mm)
Net Weight	1.17 lb(US) (0.53 kg)
Web services	Web server
Compatibility code	LTMR

## Environment

Standards	IACS E10 IEC 60947-4-1 UL 508 EN 60947-4-1 CSA C22.2 No 14
Product Certifications	ABS KERI BV EAC CSA GL C-tick ATEX UL RMRoS NOM CCC DNV RINA LROS (Lloyds register of shipping)
Protective treatment	12 x 24 hour cycles EN/IEC 60068-2-30 48 h EN/IEC 60070-2-11 TH EN/IEC 60068
Fire resistance	1202 °F (650 °C) EN/IEC 60695-2-12 1760 °F (960 °C) UL 94
Ambient air temperature for operation	-4...140 °F (-20...60 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Operating altitude	<= 6561.68 ft (2000 m) without derating
Mechanical robustness	Vibrations mounted on symmetrical rail1 Gn, 5...300 Hz EN/IEC 60068-2-6 Vibrations plate mounted4 Gn, 5...300 Hz EN/IEC 60068-2-6 Shocks half sine wave acceleration15 Gn for 11 ms EN/IEC 60068-2-27
IP Degree of Protection	IP20

## Ordering and shipping details

Category	22338-SOLID STATE OVERLOAD RELAYS
Discount Schedule	I12
GTIN	3389119404631
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.83 in (7.200 cm)
Package 1 Width	3.94 in (10.000 cm)
Package 1 Length	5.35 in (13.600 cm)
Package 1 Weight	18.48 oz (524.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	12.33 lb(US) (5.594 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------