Product data sheet Characteristics

VW3M9405

Cable, Lexium 32i, preassembled for STO safety function, 5 m, M8





Main	
Range of Product	Lexium 32i
Product or Component Type	Cable
Accessory / separate part category	Connection accessory
Product compatibility	Connector module VW3M91 safe torque off safety function Connector module VW3M92 safe torque off safety function

Complementary

Cable length	16.40 ft (5 m)	
Electrical connection	M8 female connector, 1 Free end, 1	
Cable composition	3 x 0.34 mm²	
Standards	IEC 61800-5-2	
Wire colour	White STO_A Brown STO_B Green STO_COM	
Net Weight	0.41 lb(US) (0.184 kg)	

Ordering and shipping details

<u> </u>		
Category	18289-LEXIUM INTEGRATED DRIVES ACC	
Discount Schedule	PC56	
GTIN	3606480595585	
Returnability	No	
Country of origin	CZ	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	5.91 in (15.0 cm)
Package 1 Length	6.30 in (16.0 cm)
Package 1 Weight	6.49 oz (184.0 g)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	5.27 lb(US) (2.392 kg)
Package 3 Height	11.81 in (30 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes