



Main

Range	ClimaSys
Product name	ClimaSys CR
Product or Component Type	Resistance heater
Power range	20 W
Input voltage	12...24 V DC
Electrical connection	Cable 2 x 0.75 mm ² 11.81 in (300 mm)

Complementary

Operating position	Vertical
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
IP Degree of Protection	IP20
Product Certifications	UL VDE
Material	Body extruded aluminium
Condition of use	Air sealed enclosure Heaters must be installed with a thermal controller Electrical protection is needed
Fixing Mode	By clips
Mounting Support	35 mm DIN rail

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480152122
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.31 in (13.5 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	2.76 in (7 cm)
Package 1 Weight	5.64 oz (160 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Height	3.15 in (8 cm)
Package 2 Width	2.17 in (5.5 cm)
Package 2 Length	1.18 in (3 cm)
Package 2 Weight	5.64 oz (160 g)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------