Product data sheet Characteristics

M9XCA137

Multi9 - comb busbar - 1L with Aux - 18 mm pitch - 37 modules - 80A

Main	
Range	Multi9
Product or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	37

Complementary

Number of ways	24 ways Aux + 1 L	
Poles configuration for 1 way	1 x 1P	
Connection pitch	0.71 in (18 mm)	
Connector type	tooth	
Distance between way	1.06 in (27 mm)	
Insulation	Insulated	
Device presentation	Cuttable	
[le] rated operational current	80 A 104 °F (40 °C)	
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N	
[Ui] rated insulation voltage	1000 V AC 50/60 Hz UL 508	
Mounting location	Top tunnel type terminals	
9 mm pitches	74	
Width	26.22 in (666 mm)	
Color	Light gray RAL 7035)	
Range compatibility	Multi 9 (Multi9 C60BP)	

Environment

Standards	UL 508	
Fire resistance	1760 °F (960 °C) 30 s) IEC 60695-2-1	
Pollution degree	3	
IP degree of protection	IP20 with end-pieces and tooth covers	

Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192905
Returnability	Yes

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.83 in (2.100 cm)
Package 1 Width	39.37 in (100.000 cm)
Package 1 Length	2.40 in (6.100 cm)
Package 1 Weight	24.80 oz (703.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	3.74 in (9.500 cm)
Package 2 Width	4.72 in (12.000 cm)
Package 2 Length	42.72 in (108.500 cm)
Package 2 Weight	8.37 lb(US) (3.796 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	35
Package 3 Height	44.09 in (112.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	47.24 in (120.000 cm)
Package 3 Weight	85.04 lb(US) (38.572 kg)

Offer Sustainability

Office Oddital lability	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.