LAD6K10M CONTACTOR MECH. LATCH CONTACT BLOCK IEC





Main	
Range	TeSys
Product or Component Type	Mechanical latch block
Product compatibility	LC1D09D38 AC/DC LC1DT20DT40 AC/DC LC1D40AD80A 3 phase AC/DC LC1DT60A 3 phases + neutral AC/DC LC1DT80A 3 phases + neutral AC/DC
[Uc] control circuit voltage	220/240 V AC 50/60 Hz 220/240 V DC

Complementary

Mounting LocationFront sideTripping controlElectrical Manual[Ui] rated insulation voltage690 V IEC 60947-5-1Power required in VA25 ACPower required in W30 W DCMechanical durability500000 cyclesMaximum operating rate1200 cyc/hOn-load factor10 %Net Weight0.15 lb(US) (0.07 kg)	Complementary		
Manual [Ui] rated insulation voltage 690 V IEC 60947-5-1 Power required in VA 25 AC Power required in W 30 W DC Mechanical durability 500000 cycles Maximum operating rate 1200 cyc/h On-load factor 10 %	Mounting Location	Front side	
Power required in VA 25 AC Power required in W 30 W DC Mechanical durability 500000 cycles Maximum operating rate 1200 cyc/h On-load factor 10 %	Tripping control		
Power required in W 30 W DC Mechanical durability 500000 cycles Maximum operating rate 1200 cyc/h On-load factor 10 %	[Ui] rated insulation voltage	690 V IEC 60947-5-1	
Mechanical durability 500000 cycles Maximum operating rate 1200 cyc/h On-load factor 10 %	Power required in VA	25 AC	
Maximum operating rate 1200 cyc/h On-load factor 10 %	Power required in W	30 W DC	
On-load factor 10 %	Mechanical durability	500000 cycles	
	Maximum operating rate	1200 cyc/h	
Net Weight 0.15 lb(US) (0.07 kg)	On-load factor	10 %	
	Net Weight	0.15 lb(US) (0.07 kg)	

Environment

Product Certifications	UL CSA	
IP degree of protection	IP2XVDE 0106	
Protective treatment	THIEC 60068	
Ambient Air Temperature for Operation	-13131 °F (-2555 °C)	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	112
GTIN	3389110842395
Returnability	No
Country of origin	FR

Packing Units

PCE	
1	
1.77 in (4.500 cm)	
1.97 in (5.000 cm)	
2.56 in (6.500 cm)	
3.46 oz (98.000 g)	
	1 1.77 in (4.500 cm) 1.97 in (5.000 cm) 2.56 in (6.500 cm)

Unit Type of Package 2	S01
Number of Units in Package 2	32
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	7.21 lb(US) (3.270 kg)

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
[™] Yes
Product Environmental Profile
☑ End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months	