VW3S8202R30

cable for pulse/direction signal, Lexium SD3, 24V, shielded, 3m



Main Accessory / separate Cable for pulse/direction signal part designation Accessory / Separate Connecting cable Part Type Accessory / separate Connection accessories part category Accessory / separate Between stepper drive SD326 and external impulsion part destination generator Range Compatibility Lexium SD3 Type of Cable Shielded cable

9.84 ft (3 m)

Complementary

Product Compatibility	SD326
[Uc] control circuit voltage	24 V
Electrical connection	1 connector 24-pole Molex SD326)
	Cable end open external impulsion generator)

Cable length

Ordering and shipping details

Category	18286-STEPPER ACCESSORIES
Discount Schedule	PC55
GTIN	3389119224628
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	9.84 in (25.0 cm)
Package 1 Length	10.24 in (26.0 cm)
Package 1 Weight	10.23 oz (290.0 g)
Unit Type of Package 2	S04
Number of Units in Package 2	30
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	21.94 lb(US) (9.952 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

Contractual warranty

Contraction Warranty	
Warranty	18 months