## Product data sheet Characteristics

### 990NAD21130

# Modbus Plus drop cable - between Momentum I/O sub-base and T- junction - 6 m



Main		
Accessory / separate part category	Connection accessories	
Accessory / Separate Part Type	Drop connection cable	
Accessory / separate part designation	Modbus Plus drop cable	
Accessory / separate part destination	Modbus Plus network	

#### Complementary

Complementary		
Product Compatibility	990NAD23020	
	990NAD23000	
	490NRP25300	
	990NAD23010	
	990NAD23021	
	NWBP85002	
	STBNMP2212	
	140CPU43412U	
	140CPU31110	
Range Compatibility	Modicon Momentum automation platform	
	Modicon Premium automation platform	
	Advantys STB distributed I/O solutions	
	Lexium 15	
	Modicon Quantum automation platform	
Cable length	19.69 ft (6 m)	
Electrical connection	1 male connector SUB-D 9 elbowed communication module side	
	Free end local site tap side	
Net Weight	1.17 lb(US) (0.53 kg)	

#### Ordering and shipping details

Category	18150-QUANTUM CONTROLLERS,HSBY,COMM.
Discount Schedule	PC21
GTIN	3389110078282
Returnability	No :
Country of origin	PT

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.98 in (2.500 cm)
Package 1 Width	8.23 in (20.900 cm)
Package 1 Length	9.76 in (24.800 cm)
Package 1 Weight	9.81 oz (278.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)

Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	15.32 lb(US) (6.950 kg)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warranty	18 months