LXD1Q7

Contactor coil, TeSys Deca, LXD1, 380V AC 50/60Hz for 9...38A contactor





Main Range **TeSys Product or Component** Contactor coil Type Device short name LXD1 Control circuit type AC 50/60 Hz [Uc] control circuit 380 V AC 50/60 Hz voltage 1551 Ohm 68 °F (20 °C) Average resistance Inductance of closed 55 H circuit LC1DT20...DT40 **Product Compatibility** CAD LC1D09...D38 Mechanical durability 9 Mcycles

3600 cyc/h 140 °F (60 °C)

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out 0.30.6 Uc 50/60 Hz 140 °F (60 °C)) Operational 0.81.1 Uc 50 Hz 140 °F (60 °C)) Operational 0.851.1 Uc 60 Hz 140 °F (60 °C))	
Inrush power in VA	70 VA 60 Hz 0.75 68 °F (20 °C)) 70 VA 50 Hz 0.75 68 °F (20 °C))	
Hold-in power consumption in VA	7.5 VA 60 Hz 0.3 68 °F (20 °C)) 7 VA 50 Hz 0.3 68 °F (20 °C))	
Heat dissipation	23 W 50/60 Hz	

Maximum operating rate

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net Weight	0.15 lb(US) (0.07 kg)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	l12
GTIN	3389110467925
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.57 in (4.0 cm)	
Package 1 Width	1.77 in (4.5 cm)	
Package 1 Length	2.48 in (6.3 cm)	
Package 1 Weight	2.47 oz (70.0 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	100	
Package 2 Height	5.91 in (15.0 cm)	

Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	15.91 lb(US) (7.218 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
PVC free	Yes

Contractual warranty

Contracted Warranty		
Warranty	18 months	