



NOTES:

1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL REGULATIONS.
2. REFER TO PRODUCT DOCUMENTATION FOR ADDITIONAL DETAILS PRIOR TO INSTALLATION AND SITE PREPARATION WORK.
3. ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
4. NET WEIGHT OF THE UNIT IS 35 kg [76 lb].
5. CABLE ENTRY/EXIT IS FROM BOTTOM OF THE UNIT.

⚠️ MAXIMUM 247mm IS THE RECOMMENDED DEPTH OF EQUIPMENT TO BE MOUNTED TO THE RAIL, FOR THE EIA RAIL TO SWING OPEN WITHOUT INTERFERENCE.

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.



TITLE: NetShelter Wall Rack VDM 16U Swing Chassis D400 GENERAL ARRANGEMENT

PROJECT: SUBMITTAL DRAWINGS **SHEET:** 1 OF 1

DWG NO: NSYVDM16U4P	REV: 0
DRAWN BY: DIBYA	22-FEB-22
ENGINEER: FARRUKH SYED	23-FEB-22
APPROVED BY: GUILLERMO	23-FEB-22
ANGLE PROJECTION	