



Main

Range of Product	PacDrive 3
Product or Component Type	Double drive
Device short name	LXM 62

Complementary

Product compatibility	Servo motor SHS Servo motor SH3 2.17 in (55 mm), 1 optimized in terms of torque and speed Servo motor SH3 2.17 in (55 mm), 2 optimized in terms of torque and speed Servo motor SH3 2.17 in (55 mm), 3 optimized in terms of torque and speed Servo motor SH3 2.76 in (70 mm), 1 optimized in terms of torque and speed Servo motor SH3 2.76 in (70 mm), 2 optimized in terms of high torque Servo motor SH3 2.76 in (70 mm), 3 optimized in terms of high torque Servo motor SH3 3.94 in (100 mm), 1 optimized in terms of high torque Servo motor MH3 2.76 in (70 mm), 1 optimized in terms of torque and speed
Phase	Single phase Three phase
[Us] rated supply voltage (through power supply module)	400 V three phase - 10...10 % 230 V three phase - 10...10 % 230 V single phase - 10...10 %
Supply frequency	50/60 Hz +/-5 %
Continuous output current	2 A 4 kHz
Output current 3s peak	6 A 4 kHz
Continuous power	0.95 kW
Nominal power	0.95 kW
Overvoltage category	III
Electrical connection	Terminal 0.2...15 mm ² , AWG 24...AWG 16 CN4) Terminal 0.5...16 mm ² , AWG 20...AWG 6 CN5) Terminal 0.75...16 mm ² , AWG 18...AWG 6 CN6) Terminal 0.2...6 mm ² , AWG 24...AWG 10 CN7)
Tightening torque	CN1 22.13 lbf.in (2.5 N.m)
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Physical interface	SERCOS III
Net Weight	6.61 lb(US) (3 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN/ISO 13849-2 CSA C22.2 No 14 EN/ISO 13849-1 EN 62061 UL 508C EN 61800-5-1 EN 61800-5-2 IEC 62061 IEC 61508 EN 61800-3
Product Certifications	CSA CE EAC UL TÜV
IP degree of protection	IP20 EN/IEC 60529
Vibration resistance	10 m/s ² EN/IEC 60721-3-3
Shock resistance	100 m/s ² EN/IEC 60721-3-3
Pollution degree	2 EN/IEC 61800-5-2
Environmental characteristic	3K3 IEC 60721-3-3
Relative humidity	5...85 %
Ambient Air Temperature for Operation	41...131 °F (5...55 °C)

Ordering and shipping details

Category	18356-PACDRIVE3 LEXIM62 SERVO DRIVES
Discount Schedule	PC52
GTIN	3606485317786
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.02 in (10.2 cm)
Package 1 Width	13.07 in (33.2 cm)
Package 1 Length	16.73 in (42.5 cm)
Package 1 Weight	8.81 lb(US) (3.998 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	29.53 in (75.0 cm)
Package 2 Width	31.50 in (80.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	75.38 lb(US) (34.192 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
