HU661AWK

Safety switch, heavy duty, non fusible, 30A, 6 poles, 30 hp, 600 VAC/DC, NEMA 12





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	6
Current Rating	30 A
Voltage Rating	600 V AC
Enclosure Rating	NEMA 3R/12 galvannealed steel
Motor power hp	10 Hp at 240 V AC 50-60 Hz for 3 phase motors 20 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 hp at 600 V AC 50-60 Hz for 3 phase motors

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	6-wire
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	6.8 in (172.72 mm)
Width	16.13 in (409.70 mm)
Height	20.5 in (520.70 mm)
Net Weight	30.86 lb(US) (14 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00116-H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	785901868354
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.40 in (18.796 cm)	
Package 1 Width	16.70 in (42.418 cm)	
Package 1 Length	25.70 in (65.278 cm)	
Package 1 Weight	29.85 lb(US) (13.54 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Marranty	18 months	
vvarranty	18 months	
•		