



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XU5M18MA230K



Telemecanique
Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression:
 Diffuse: 400.0 mm (15.7 in)
 Polarized Retroreflective:
 Thru Beam:
 Retroreflective:
 Circuit Type:
 Output Mode: Light Operate
 Power: AC/DC
 Voltage Range: 24-240
 Max Load: 200 mA
 Max Switching Frequency : 25 Hz
 Temp Range: -25° to 55° C (-13° to 131° F)
 NEMA Type: 4X (indoor use only)
 IP Rating: 67
 Standards: UL, CE Rohs

Specification:

Sensor Type: Proximity Diffuse
 Description: Photoelectric, Proximity Diffuse, 18 mm Barrel, 24-240
 Body Style: Barrel
 Diameter: mm
 Housing Material: Metal - NPB
 Face Material: PMMA
 Adjustment: Yes
 Cable Size:
 Connector Type: 3-pin U20
 Special Features: