



### Overview

Lead time	Usually in Stock
-----------	------------------



### Main

Product or Component Type	Replacement battery cartridge
Number of cables	1
Battery Type	Lead-Acid battery
Provided Equipment	All required connectors Battery recycling guide Metallic battery tray or enclosure Reusable packaging Installation guide

### Physical

Height	4.25 in (10.8 cm)
Width	6.50 in (16.5 cm)
Depth	22.52 in (57.2 cm)
Net Weight	54.12 lb(US) (24.55 kg)
Mounting Mode	Not rack-mountable

### Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cartridge
Battery Voltage	48V
Additional information	The SU48R3XLBP requires two(2) RBC27's.
RBC Quantity	1

## Ordering and shipping details

GTIN	731304099840
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.98 in (27.9 cm)
Package 1 Width	12.24 in (31.1 cm)
Package 1 Length	29.02 in (73.7 cm)
Package 1 Weight	58.11 lb(US) (26.36 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------