# LAD4RCU

TeSys D, RC transient suppressor, 110 to 250 VAC, for LC1D09 to LC1D38, mounts on right side in cavity





| Main                         |  |
|------------------------------|--|
| Range                        | TeSys  |
| Device short name            | LAD4   |
| Product or Component<br>Type | Suppressor module  |
| Product compatibility        | 3P LC1D09D38<br>4P LC1DT20DT40<br>4P LC1D098D258<br>CAD32, CAD50 |

Complementary

| Mounting Location            | Side                   |  |
|------------------------------|------------------------|--|
| Mounting Mode                | By clips               |  |
| Suppressor technology        | RC circuit             |  |
| [Uc] control circuit voltage | 110250 V AC            |  |
| Maximum peak voltage         | 3 Uc                   |  |
| Net Weight                   | 0.03 lb(US) (0.012 kg) |  |

#### Environment

| Standards                             | IEC 60947-5-1          |  |
|---------------------------------------|------------------------|--|
|                                       | EN 60947-5-1           |  |
|                                       | CSA C22.2 No 60947-5-1 |  |
|                                       | UL 60947-5-1           |  |
|                                       | GB/T 14048.5           |  |
| Product Certifications                | UL                     |  |
|                                       | CSA                    |  |
| IP degree of protection               | IP2XIEC 60529          |  |
| Ambient Air Temperature for Operation | -13131 °F (-2555 °C)   |  |
| Ambient Air Temperature for Storage   | -40176 °F (-4080 °C)   |  |

#### Ordering and shipping details

| Category          | 22341-CONTACTOR,D,K,&F ACCESS |
|-------------------|-------------------------------|
| Discount Schedule | l12                           |
| GTIN              | 3389110385458                 |
| Returnability     | Yes                           |
| Country of origin | FR                            |

## **Packing Units**

| PCE                 |  |
|---------------------|--|
| 1                   |  |
| 0.43 in (1.100 cm)  |  |
| 3.94 in (10.000 cm) |  |
| 1.97 in (5.000 cm)  |  |
| 0.49 oz (14 g)      |  |
|                     | 1<br>0.43 in (1.100 cm)<br>3.94 in (10.000 cm)<br>1.97 in (5.000 cm) |

| Unit Type of Package 2       | S01                       |
|------------------------------|---------------------------|
| Number of Units in Package 2 | 70                        |
| Package 2 Height             | 5.91 in (15.000 cm)       |
| Package 2 Width              | 5.91 in (15.000 cm)       |
| Package 2 Length             | 15.75 in (40.000 cm)      |
| Package 2 Weight             | 2.66 lb(US) (1.207 kg)    |
| Unit Type of Package 3       | P06                       |
| Number of Units in Package 3 | 2240                      |
| Package 3 Height             | 29.53 in (75.000 cm)      |
| Package 3 Width              | 23.62 in (60.000 cm)      |
| Package 3 Length             | 31.50 in (80.000 cm)      |
| Package 3 Weight             | 107.01 lb(US) (48.539 kg) |

## Offer Sustainability

| Sustainable offer status   | Green Premium product  |
|----------------------------|--|
| REACh Regulation           | ☑ REACh Declaration  |
| REACh free of SVHC         | Yes  |
| EU RoHS Directive          | Compliant EPEU RoHS Declaration  |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | China RoHS Declaration   |
| RoHS exemption information | ₫Yes   |
| Environmental Disclosure   | Product Environmental Profile  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|