M9A26946

Multi9 - shunt trip release with OC - MX + OF - 110/415 V AC - 110/130 V DC





Main

Range of product	Multi9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[le] rated operational current	3 A 415 V AC 6 A <= 240 V AC
[Uc] control circuit voltage	110415 V AC 50/60 Hz 110130 V DC
9 mm pitches	2

Complementary

Complementary	
Range compatibility	Multi 9 (Multi9 C60) C60BP Multi 9 (Multi9 C60) C60BPR Multi 9 (Multi9 C60) C60SP Multi 9 (Multi9 GFP) GFP Multi 9 (Multi9 C60H-DC) C60H-DC
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Height	3.25 in (82.5 mm)
Width	0.71 in (18 mm)
Depth	2.68 in (68 mm)
Net Weight	0.14 lb(US) (0.065 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.00 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.00 in² (1.5 mm²) AWG 16) - rigid
Wire stripping length	0.35 in (9 mm) bottom
Tightening torque	8.85 lbf.in (1 N.m) bottom

Environment

2.11 Total of the control of the con		
Standards	EN/IEC 60947-1	
Product Certifications	CSA	
	CCC	
	UL	
	PCT	
	UR	
Pollution degree	3	
Ambient Air Temperature for Operation	-13122 °F (-2550 °C)	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	

Ordering and shipping details

Category	00948-M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	3606480639074
Returnability	Yes
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3 cm)
Package 1 Width	3.07 in (7.8 cm)
Package 1 Length	3.70 in (9.4 cm)
Package 1 Weight	2.50 oz (70.9 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.35 in (8.5 cm)
Package 2 Width	3.94 in (10 cm)
Package 2 Length	10.43 in (26.5 cm)
Package 2 Weight	22.33 oz (633 g)
Unit Type of Package 3	S03
Number of Units in Package 3	32
Package 3 Height	11.81 in (30 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	6.46 lb(US) (2.932 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.