

### product type designation



### CP 1543SP-1

Communications processor CP 1543SP-1 for connection of an SIMATIC S7-ET 200SP to Industrial Ethernet; Security (firewall and VPN) Open IE communication (TCP/IP, ISO-on-TCP, UDP) PG/OP, S7 routing, IP broadcast/multicast, SNMPV1/V3, DHCP, secure email, IPV4/IPV6, support of SINEMA Remote Connect with autoconfiguration, time-of-day synchronization via NTP, access to web server of CPU, bus adapter required.

### transfer rate

transfer rate	
<ul style="list-style-type: none"> <li>at the 1st interface</li> </ul>	10 ... 100 Mbit/s

### interfaces

number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
<ul style="list-style-type: none"> <li>at the 1st interface / according to Industrial Ethernet</li> </ul>	2
type of electrical connection	
<ul style="list-style-type: none"> <li>at the 1st interface / according to Industrial Ethernet</li> </ul>	via ET 200SP bus adapter (RJ45, FC, SCRJ), integrated switch

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	19.2 ... 28.8 V
power loss [W]	6 W

### ambient conditions

ambient temperature	
<ul style="list-style-type: none"> <li>for vertical installation / during operation</li> <li>for horizontally arranged busbars / during operation</li> <li>during storage</li> <li>during transport</li> </ul>	-30 ... +50 °C -30 ... +60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20

### design, dimensions and weights

width	60 mm
height	117 mm
depth	74 mm
net weight	0.18 kg
fastening method	
<ul style="list-style-type: none"> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes

### product features, product functions, product components / general

number of units	
<ul style="list-style-type: none"> <li>per CPU / maximum</li> <li>note</li> </ul>	2 2 CPs can be plugged in per CPU, simultaneous operation with BA Send and CM DP is possible

### performance data / open communication

number of possible connections / for open communication	
<ul style="list-style-type: none"> <li>by means of T blocks / maximum</li> </ul>	32
data volume	

<ul style="list-style-type: none"> <li>as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum</li> </ul>	65536 byte
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>maximum</li> </ul>	16
<ul style="list-style-type: none"> <li>with OP connections / maximum</li> </ul>	16
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	32
<b>performance data / IT functions</b>	
number of possible connections	
<ul style="list-style-type: none"> <li>as email client / maximum</li> </ul>	1
<b>product functions / management, configuration, engineering</b>	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>SNMP v3</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>LLDP</li> </ul>	Yes
configuration software	
<ul style="list-style-type: none"> <li>required</li> </ul>	STEP 7 Professional V14 (TIA Portal) or higher
identification & maintenance function	
<ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>I&amp;M1 - higher level designation/location designation</li> </ul>	Yes
<b>product functions / diagnostics</b>	
product function / web-based diagnostics	Yes; via ET 200SP CPU
<b>product functions / security</b>	
firewall version	stateful inspection
product function / with VPN connection	IPsec, SINEMA RC
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1
number of possible connections / with VPN connection	4
product function	
<ul style="list-style-type: none"> <li>switch-off of non-required services</li> </ul>	Yes
<ul style="list-style-type: none"> <li>blocking of communication via physical ports</li> </ul>	Yes
<ul style="list-style-type: none"> <li>log file for unauthorized access</li> </ul>	Yes
<b>product functions / time</b>	
product function / SICLOCK support	Yes
product function / pass on time synchronization	No
protocol / is supported	
<ul style="list-style-type: none"> <li>NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>NTP (secure)</li> </ul>	Yes
time synchronization	
<ul style="list-style-type: none"> <li>from NTP-server</li> </ul>	Yes
<b>standards, specifications, approvals / hazardous environments</b>	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx-Download-Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For

the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>.  
(V3.4)

last modified:

7/7/2022 