



SIMATIC DP, Basic module BM 141 ET 200ECO: 16 DI 24 V DC; 8xM12, Duplicate assignment, Degree of protection IP65/67; Connection block 6ES7194-3AA00-0.A0 separately order

General information	
Vendor identification (VendorID)	80DAh
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from supply voltage 1L+, max.	70 mA; Typical
Encoder supply	
Number of outputs	8
Type of output voltage	24 V DC
Short-circuit protection	Yes; Electronic
Output current	
<ul style="list-style-type: none"> Rated value 	1 A; Aggregate current up to 55 °C
Power loss	
Power loss, typ.	3.6 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	16
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) for signal "0" for signal "1" 	24 V -3 to +5V 13 to 30V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	3 ms; Typical
— at "1" to "0", max.	3 ms; Typical
Cable length	
<ul style="list-style-type: none"> unshielded, max. 	30 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> 2-wire sensor — permissible quiescent current (2-wire sensor), max. 	Yes 1.5 mA
Interfaces	

PROFIBUS DP	
• Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s
Protocols	
PROFIBUS DP	Yes
Interrupts/diagnostics/status information	
Alarms	No
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Channel fault indicator F (red)	No
Potential separation	
between PROFIBUS DP and all other circuit components	Yes
Potential separation digital inputs	
• between the channels	No
Permissible potential difference	
between different circuits	75 V DC/60 V AC
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP degree of protection	IP65/67
connection method / header	
Design of electrical connection	4/5-pin M12 circular connectors
Dimensions	
Width	60 mm
Height	210 mm
Depth	28 mm
Weights	
Weight, approx.	210 g
last modified:	12/18/2020 