

product type designation

product description

Distance piece 20 mm MOBY D/ E, RF300

Spacer for establishing the necessary distance from the RFID tags to metal
MOBY D/E, RF300 spacer for MDS D100/MDS E600/611, RF360T, 20 mm; in connection with fixing lug 6GT2190-0AB00 (for metal-free room).



suitability for use

Can be secured using screws, rivets or cable ties

mechanical data

material PA 6
color anthracite

ambient conditions

ambient temperature

- during operation -25 ... +75 °C
- during storage -40 ... +85 °C
- during transport -40 ... +85 °C

design, dimensions and weights

width 62 mm
height 24 mm
depth 110 mm

further information / internet-Links

Internet-Link

- to website: TIA Selection Tool <http://www.siemens.com/tia-selection-tool>
- to the website: IWLAN <http://www.siemens.com/iwlan>
- to website: Industrial communication <http://www.siemens.com/ident/rfid>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Selection guide for cables and connectors <https://sie.ag/2QdlxcP>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx-Download-Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

5/20/2021