



SIMATIC S7-1500, F digital input module, F-DI 16x 24 V DC PROFIsafe;  
35 mm width; up to PL E (ISO 13849-1)/ SIL 3 (IEC 61508)

General information	
Product type designation	F-DI 16x24VDC
Firmware version	
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 SP1 with HSP 0086
Operating mode	
<ul style="list-style-type: none"> <li>DI</li> </ul>	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption (rated value)	50 mA; without load
Current consumption, max.	60 mA; without load
Encoder supply	
Number of outputs	4
Short-circuit protection	Yes; Electronic (response threshold 0.7 A to 1.8 A)
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	Yes; min. L+ (-1.5 V)
<ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	300 mA; Max. 100 mA when mounted vertically
Power	
Power available from the backplane bus	0.9 W
Power loss	
Power loss, typ.	4.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	9 byte; S7-300/400F CPU, 8 byte
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	5 byte; S7-300/400F CPU, 4 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> <li>Electronic coding element type F</li> </ul>	Yes
Digital inputs	
Number of digital inputs	16

Source/sink input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
<b>Input voltage</b>	
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+15 to +30 V
<b>Input current</b>	
• for signal "1", typ.	3.7 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes
— at "0" to "1", min.	0.4 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.4 ms
— at "1" to "0", max.	20 ms
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	500 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
• Hardware interrupt	No
<b>Diagnoses</b>	
• Monitoring the supply voltage	Yes
• Wire-break	No
• Short-circuit	Yes
• Group error	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	Yes
<b>Highest safety class achievable in safety mode</b>	
• Performance level according to ISO 13849-1	PL <sub>e</sub>
• SIL acc. to IEC 61508	SIL 3
<b>Probability of failure (for service life of 20 years and repair time of 100 hours)</b>	
— Low demand mode: PFD <sub>avg</sub> in accordance with SIL3	< 5.00E-05
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>Weights</b>	
Weight, approx.	280 g
<b>last modified:</b>	10/7/2021 

