



DS1E-X for ET200S High Feature DOL starter Setting range 2.4...16 A
 Mechanical switching Electronic protection AC-3, up to 7.5 kW / 400 V
 expandable for Brake control module 2DI module 2DI module Motor starter
 ES Circuit breaker signaling parameterizable DPV 1-capable
 PROFIENERGY-capable to PN

product brand name	SIMATIC
product designation	Motor starters
design of the product	direct starter
product type designation	ET 200S

General technical data

trip class	CLASS 5, 10, 15, 20
product function on-site operation	Yes
insulation voltage rated value	500 V
degree of pollution	3 at 400 V, 2 at 500 V according to IEC60664 (IEC61131)
surge voltage resistance rated value	6 kV
maximum permissible voltage for safe isolation between main and auxiliary circuit	400 V
shock resistance	5g / 11 ms
vibration resistance	2g
mechanical service life (operating cycles) of the main contacts typical	100 000
type of assignment	2
reference code according to IEC 81346-2	Q
Substance Prohibitance (Date)	05/28/2009
product function	Yes
<ul style="list-style-type: none"> • direct start • reverse starting 	No
product component motor brake output	Yes
product feature	No
<ul style="list-style-type: none"> • brake control with 230 V AC • brake control with 24 V DC • brake control with 180 V DC • brake control with 500 V DC 	No
product extension braking module for brake control	Yes
product function short circuit protection	Yes
design of short-circuit protection	circuit-breakers
maximum short-circuit current breaking capacity (Icu)	50 kA
<ul style="list-style-type: none"> • at 400 V rated value 	

Electromagnetic compatibility

EMC emitted interference according to IEC 60947-1	CISPR11, ambience A (industrial sector)
EMC immunity according to IEC 60947-1	corresponds to degree of severity 3, ambience A (industrial sector)
conducted interference	
<ul style="list-style-type: none"> • due to burst according to IEC 61000-4-4 • due to conductor-earth surge according to IEC 61000-4-5 • due to conductor-conductor surge according to IEC 61000-4-5 	2 kV on voltage supply, inputs and outputs 2 kV (U > 24 V DC) 1 kV (U > 24 V DC)

field-based interference according to IEC 61000-4-3	80 MHz ... 1 GHz 10 V/m, 1.4 GHz ... 2 GHz 3 V/m, 2 GHz ... 2.7 GHz 1 V/m
Safety related data	
B10 value with high demand rate according to SN 31920	1 000 000
proportion of dangerous failures	
• with low demand rate according to SN 31920	50 %
• with high demand rate according to SN 31920	75 %
failure rate [FIT]	
• with low demand rate according to SN 31920	100 FIT
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe
Main circuit	
number of poles for main current circuit	3
design of the switching contact	electromechanical
adjustable current response value current of the current-dependent overload release	2.4 ... 16 A
type of the motor protection	solid-state
operating voltage rated value	200 ... 400 V
operating frequency 1 rated value	50 Hz
operating frequency 2 rated value	60 Hz
relative positive tolerance of the operating frequency	10 %
relative negative tolerance of the operating frequency	10 %
operating range relative to the operating voltage at AC at 50 Hz	200 ... 440 V
operational current	
• at AC-3 at 400 V rated value	16 A
operating power at AC-3 at 400 V rated value	7.5 kW
operating power for 3-phase motors at 400 V at 50 Hz	1.1 ... 7.5 kW
Inputs/ Outputs	
product function	
• digital inputs parameterizable	Yes
• digital outputs parameterizable	No
number of digital inputs	2
number of sockets	
• for digital output signals	0
• for digital input signals	0
Supply voltage	
type of voltage of the supply voltage	DC
supply voltage 1 at DC	24 ... 24 V
supply voltage 1 at DC rated value	
• minimum permissible	20.4 V
• maximum permissible	28.8 V
Control circuit/ Control	
type of voltage of the control supply voltage	DC
control supply voltage at DC rated value	20.4 ... 28.8 V
control supply voltage 1	
• at DC rated value	20.4 ... 28.8 V
• at DC	24 ... 24 V
Installation/ mounting/ dimensions	
mounting position	vertical, horizontal
fastening method	pluggable on terminal module
height	290 mm
width	65 mm
depth	150 mm
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity during operation	5 ... 95 %

Communication/ Protocol

protocol is supported

- PROFIBUS DP protocol
- PROFINET protocol

Yes

Yes

design of the interface PROFINET protocol

Yes

product function bus communication

Yes

protocol is supported AS-Interface protocol

No

product function

- supports PROFIenergy measured values
- supports PROFIenergy shutdown

Yes

Yes

address space memory of address range

- of the inputs
- of the outputs

2 byte

2 byte

type of electrical connection

- of the communication interface
- for communication transmission

via backplane bus

via backplane bus

Connections/ Terminals

type of electrical connection for main current circuit

screw-type terminals

type of electrical connection

- 1 for digital input signals
- 2 for digital input signals

using control module

using control module

type of electrical connection

- at the manufacturer-specific device interface
- for main energy infeed
- for load-side outgoing feeder
- for main energy transmission
- for supply voltage line-side
- for supply voltage transmission

plug

screw-type terminals

Screw-type terminals

via energy bus

via backplane bus

via backplane bus

UL/CSA ratings

operating voltage at AC at 60 Hz according to CSA and UL rated value

600 V

Certificates/ approvals

General Product Approval

EMC



[Confirmation](#)



Declaration of Conformity

other

Dangerous Good



[Confirmation](#)

[Transport Information](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)




<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RK1301-0CB10-0AB4>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RK1301-0CB10-0AB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1301-0CB10-0AB4>



last modified:

12/15/2020 