



Figure similar

The new part, as of 01.01.2015, is blocked for delivery. Spare part can continue to be purchased as required, but price may deviate from new part. Further information under SIMATIC current entry ID: 109486162. For questions, the familiar contact persons are available to you. SIMATIC MP 377 12" Key Multi Panel, Windows CE 5.0 12" color TFT display 12 MB configuration memory configurable from WinCC flexible 2007 New key aluminum front with uniform clamps

General information	
Product type designation	MP377 12" key
Display	
Design of display	TFT
Screen diagonal	12.1 in
Color display	Yes
Number of colors	65 536
Resolution (pixels)	
• Horizontal image resolution	800 pixel
• Vertical image resolution	600 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Membrane keyboard
Keyboard fonts	
• Function keys	
— Number of function keys	36
— Number of function keys with LEDs	36
• System keys	Yes
— Number of system keys	38
• Numeric keyboard	Yes
• alphanumeric keyboard	Yes
• hexadecimal keyboard	Yes
• Multi-key operation	Yes
— Number of multi-key operations	2
Touch operation	
• Design as touch screen	No; without
Connection type	
• Type of connection for mouse/keyboard/barcode reader	USB / USB / USB
Installation type/mounting	
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Input current	
Current consumption (rated value)	1.5 A
Starting current inrush I ² t	4 A ² ·s
Power	
Active power input, typ.	36 W

Memory	
Type of memory	Flash / RAM
Memory available for user data	12 288 kbyte
Time of day	
Clock	
<ul style="list-style-type: none"> Type 	Hardware clock, battery backup, synchronizable
<ul style="list-style-type: none"> retentive 	Yes
<ul style="list-style-type: none"> synchronizable 	Yes
Interfaces	
Interfaces/bus type	1x RS 422, 1x RS 485, 2x Ethernet (RJ45)
Number of industrial Ethernet interfaces	2
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of USB interfaces	2; Up to 1 GB respectively
CF card slot	1x CF card slot
Multimedia card/SD card slot	1x Multimedia Card slot, up to 128 MB
With software interfaces	No
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	Yes
EtherNet/IP	Yes
MPI	Yes
Protocols (Ethernet)	
<ul style="list-style-type: none"> TCP/IP 	Yes
Protocols (terminal link)	
<ul style="list-style-type: none"> Sm@rtServer 	Yes
Further protocols	
<ul style="list-style-type: none"> MODBUS 	Yes
<ul style="list-style-type: none"> other bus systems 	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> Limit class A, for use in industrial areas 	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	NEMA 4, NEMA 12 (when installed)
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
Use in hazardous areas	
<ul style="list-style-type: none"> ATEX Zone 2 	No; certificate no longer available as of 1 October 2020
<ul style="list-style-type: none"> ATEX Zone 22 	No; certificate no longer available as of 1 October 2020
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. 	0 °C
<ul style="list-style-type: none"> max. 	50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. 	-20 °C
<ul style="list-style-type: none"> max. 	60 °C
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	90 %
Operating systems	
pre-installed operating system	Windows CE
configuration / header	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes

Configuration software	
• Configuration tool	WinCC flexible Standard Version 2007 or higher (to be ordered separately)
• STEP 7 Basic (TIA Portal)	No
• STEP 7 Professional (TIA Portal)	No
• WinCC flexible Compact	No
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes
• WinCC Advanced (TIA Portal)	Yes
• WinCC Professional (TIA Portal)	Yes
Languages	
Online languages	
• Number of online/runtime languages	16
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
Message system	
• Number of alarm classes	32
• Number of messages	4 000
• Bit messages	Yes
— Number of bit messages	4 000
• Analog messages	Yes
— Number of analog messages	200
• Telegram message procedure Alarm S	Yes
• System messages HMI	Yes
• System messages PLC	Yes
• System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...)	Yes
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Message indicator	Yes
• First/last value	Yes
Recipe management	
• Number of recipes	500
• Data records per recipe	1 000
• Entries per data record	1 000
• Recipe memory	128 KB integrated Flash, expandable
Variables	
• Number of variables per device	4 096; Configuration with WinCC flexible 2008 and higher
• Number of variables per screen	400
• Number of variables	2 000
• Initial values	2 048
• Type Date & Time	2 048
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	30 000 text elements
• Number of I/O fields per image	400
• Number of date/time fields	400
• Return	Yes

<ul style="list-style-type: none"> • Graphics object <ul style="list-style-type: none"> — Icons 	Bit maps, icons, vector graphics 2 000
Complex image objects	
<ul style="list-style-type: none"> • Status/control • dynamic objects <ul style="list-style-type: none"> — Number of objects per project — Number of curve diagrams per image • Methods • Bar graphs <ul style="list-style-type: none"> — Number of bars per chart • Sliders <ul style="list-style-type: none"> — Number of slides per image • Pointer instruments <ul style="list-style-type: none"> — Number of analog indicators per image • Limit value lines • Number of alphanumerical fields <ul style="list-style-type: none"> — alphanumeric fields per image • Number of numerical fields <ul style="list-style-type: none"> — numerical fields per image • Number of password fields • Number of visible switches per project <ul style="list-style-type: none"> — visible switches per image — hidden switches per image • Number of status switches per project <ul style="list-style-type: none"> — Number of status switches per image • Number of selector switches per project <ul style="list-style-type: none"> — Selector switches per image • Number of signal lamps per project <ul style="list-style-type: none"> — Signal lamps per image 	With SIMATIC S7 Diagrams, bar graphs, sliders, analog display, invisible buttons 2 000 20 Trend / profile 20 20 20 Yes 300 400 2 048 400 400 400 400 400 400 400 400 400 400 400
Attributes for dynamic objects	
<ul style="list-style-type: none"> • Color change • X/Y movement • Hide 	Yes Yes Yes
Lists	
<ul style="list-style-type: none"> • Number of text lists per project • Number of text lists per image • Number of entries per text list • Number of graphics lists per project • Number of graphic lists per image • Number of entries per graphics list 	500 400 256 500 400 256
Archiving	
<ul style="list-style-type: none"> • Number of archives per device • Number of measuring points per project • Number of entries per archive • Message archive • Process value archive • Archiving methods <ul style="list-style-type: none"> — Sequential archive — Short-term archive • Memory location <ul style="list-style-type: none"> — CF card — Ethernet • Data storage format <ul style="list-style-type: none"> — CSV • external evaluation • Size of archive • Online evaluation <ul style="list-style-type: none"> — using trend curves 	50 50 50 000 Yes Yes Sequential log, circular log, alarm log, process value archive Yes Yes CF card, SD/MMC card, Ethernet, USB memory stick Yes Yes CSV file, readable, e.g. with MS Excel, MS Access Yes readable, e.g. with MS Excel, MS Access, etc. depending on free memory on ext. card/stick or on free hard disk space via network drive via trends Yes
Filters	
<ul style="list-style-type: none"> • cyclic • Tolerance • Change 	Yes Yes Yes
Security	

<ul style="list-style-type: none"> • Number of user groups • Number of user rights • Password export/import 	50 32 Yes
Data carrier support	
<ul style="list-style-type: none"> • CF card • Hard disk 	Yes Yes
Logging through printer	
<ul style="list-style-type: none"> • Recording/Printing 	Alarms, report (shift report), color print, hardcopy
Transfer (upload/download)	
<ul style="list-style-type: none"> • Transfer of configuration 	MPI/PROFIBUS DP, serial, USB, Ethernet, by means of external storage medium, automatic transfer recognition
Process coupling	
<ul style="list-style-type: none"> • Connection to controller 	S5, S7-200, S7-300/400, TI 505, Win AC, PC (TCP/IP), SINUMERIK, SIMOTION, Allen Bradley (DF1), Allen Bradley (DF485), Mitsubishi (FX), OMRON (LINK/Multilink), Modicon (Modbus), further non-Siemens drivers, see chapter "System interfaces"
<ul style="list-style-type: none"> • S7-1200 	Yes
<ul style="list-style-type: none"> • S7-1500 	Yes
<ul style="list-style-type: none"> • S7-200 	Yes
<ul style="list-style-type: none"> — PPI (point-to-point) 	Yes
<ul style="list-style-type: none"> — PPI network 	Yes
<ul style="list-style-type: none"> — MPI 	Yes
<ul style="list-style-type: none"> — PROFIBUS DP 	Yes
<ul style="list-style-type: none"> • S7-300/400 	Yes
<ul style="list-style-type: none"> — MPI 	Yes
<ul style="list-style-type: none"> — PROFIBUS DP 	Yes
<ul style="list-style-type: none"> — PROFINET 	Yes
<ul style="list-style-type: none"> • S5 	Yes
<ul style="list-style-type: none"> — PROFIBUS DP 	Yes
<ul style="list-style-type: none"> • TI 505 	Yes
<ul style="list-style-type: none"> • Allen Bradley (DF1) 	Yes
<ul style="list-style-type: none"> • Allen Bradley (DF485) 	Yes
<ul style="list-style-type: none"> • Mitsubishi (FX) 	Yes
<ul style="list-style-type: none"> • Mitsubishi (MP4) 	Yes
<ul style="list-style-type: none"> • Telemecanique (Uni-Telway) 	Yes
<ul style="list-style-type: none"> • OMRON (LINK/Multilink) 	Yes
<ul style="list-style-type: none"> • Modicon (Modbus) 	Yes
<ul style="list-style-type: none"> • GE-Fanuc (SNP) 	Yes
Functions	
<ul style="list-style-type: none"> • Key repeat • TAB sequence • Calculating functions • Animate 	Yes Yes Yes Yes
Service tools/configuration aids	
<ul style="list-style-type: none"> • Backup/Restore manually • Simulation • Device switchover • Delta transfer • Monitoring function for battery and memory 	Yes Yes Yes Yes Yes
Expandability/openness	
<ul style="list-style-type: none"> • Open Platform Program 	Yes
Peripherals/Options	
Peripherals	Printer, card reader, barcode reader
SIMATIC HMI MM memory card: Multi Media Card	Yes
SIMATIC HMI SD memory card: Secure Digital memory card	Yes
USB memory	Yes
Additional software components loadable	Yes
Dimensions	
Width of the housing front	483 mm
Height of housing front	310 mm
Mounting cutout, width	450 mm
Mounting cutout, height	290 mm
Overall depth	59 mm

Weights

Weight (without packaging)

5.5 kg

last modified:

10/7/2021 