

product type designation

product description



Support MDS 439E/U 589/RF380T

Support for mounting heat-resistant transponders on a crossbar

MOBY I/U/RF300 support for heat resistant data storage medium MDS 439E/MDS U589/RF380T short version 234x 140 without shrouding cover.

suitability for use

Transponders with a diameter of 114 mm can be mounted in the support

mechanical data

material

V2A sheet

color

silver

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +220 °C

-40 ... +220 °C

-40 ... +220 °C

design, dimensions and weights

width

140 mm

height

2.5 mm

depth

234 mm

further information / internet-Links

Internet-Link

- to website: TIA Selection Tool
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/ident/rfid>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<https://sie.ag/2QdlxcP>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

5/20/2021 