

## Data sheet for Line reactor



Figure similar

MLFB-Ordering data

6SL3203-0CD25-3AA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

### Rated data

#### Input

|                  |               |
|------------------|---------------|
| Number of phases | 3 AC          |
| Line voltage     | 380 ... 480 V |

#### Output

|               |        |
|---------------|--------|
| Rated current | 63.0 A |
|---------------|--------|

### Mechanical data

#### Dimensions

|                      |                     |
|----------------------|---------------------|
| Width                | 275.0 mm (10.8 in)  |
| Height               | 455.0 mm (17.9 in)  |
| Depth                | 84.0 mm (3.3 in)    |
| Degree of protection | IP20 / UL open type |
| Net weight           | 13.0 kg (28.7 lb)   |

### Connections

#### Line side

|         |                     |
|---------|---------------------|
| Version | screw-type terminal |
|---------|---------------------|

#### Load side

|                         |                               |
|-------------------------|-------------------------------|
| Version                 | Cable                         |
| Conductor cross-section | 16.00 mm <sup>2</sup> (6 AWG) |
| Cable length            | 0.70 m (2.30 ft)              |

#### PE connection

|         |          |
|---------|----------|
| Version | M8 Screw |
|---------|----------|

### Standards

|                           |       |
|---------------------------|-------|
| Compliance with standards | cURus |
|---------------------------|-------|