

*** spare part *** connection box DP Basic for Mobile Panels
(MPI/PROFIBUS)



General information	
Product function	
• Location identifier	Yes
FH technology	
Safety evaluation through direct wiring	
• Reconnection with emergency stop circuit interruption	Yes
• Monitoring the STOP button	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.4 A
Power	
Active power input, typ.	10 W
Interfaces	
Interfaces/bus type	1x RS 232, 1x RS 422, 1x RS 485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of RS 232 interfaces	1
Number of 20 mA interfaces (TTY)	0
Connection point identification	Yes
Degree and class of protection	
IP degree of protection	IP65
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No
Use in hazardous areas	
• ATEX Zone 2	No
• ATEX Zone 22	No
• FM Class I Division 2	No
Ambient conditions	
Ambient temperature during operation	

Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	85 %
Dimensions	
Width	160 mm
Height	120 mm
Depth	70 mm
Weights	
Weight (without packaging)	0.35 kg
Other	
free hotline	Yes
Usable in the following products	
• Product 1	6AV6645-0A*
• Product 2	6AV6645-0C*
• Product 3	6AV6645-0BE02-0AX0
last modified:	11/3/2021 