



SIMOTION Drive-based Control Unit D425-2 DP; programmable motion controller; BASIC performance; interfaces: 12 DI, 16 DI/DO, 4 DRIVE-CLiQ, 2 PROFIBUS, 3 ethernet, 2 USB, 1 option slot; incl. dual fan / battery module and battery

product brand name	SIMOTION
product type designation	D425-2 DP
Performance class for motion control system	BASIC Performance
Version of the motion control system	Multiple-axis system

### PLC and motion control performance

number of axes / maximum	16
Minimum PROFIBUS cycle clock	1 ms
Minimum interpolator cycle clock	0.5 ms
Minimum servo cycle clock	0.5 ms

### Integrated drive control / header

Maximum number of axes for integrated drive control	
<ul style="list-style-type: none"> <li>• servo</li> <li>• vector</li> <li>• V/f</li> <li>• note</li> </ul>	<p>6</p> <p>6</p> <p>12</p> <p>Alternative control modes; drive control based on SINAMICS S120 CU320-2, firmware version V4.x/V5.x</p>

### Memory

RAM (work memory)	78 Mbyte
Additional RAM work memory for Java applications	20 Mbyte
RAM disk (load memory)	38 Mbyte
Retentive memory	364 kbyte
Persistent memory (user data on CF)	1.5 Gbyte

### Communication

Interfaces	
<ul style="list-style-type: none"> <li>• DRIVE-CLiQ</li> <li>• USB</li> <li>• Industrial Ethernet</li> <li>• PROFIBUS</li> <li>— note</li> <li>• PROFINET</li> </ul>	<p>4</p> <p>2</p> <p>3</p> <p>2</p> <p>Equidistant and isochronous; Can be configured as master or slave</p> <p>0</p>

### General technical data

Fan	Double fan/battery module included in scope of delivery
DC supply voltage	
<ul style="list-style-type: none"> <li>• rated value</li> <li>• minimum</li> <li>• maximum</li> </ul>	<p>24 V</p> <p>20.4 V</p> <p>28.8 V</p>
consumed current / typical	700 mA
<ul style="list-style-type: none"> <li>• note</li> </ul>	with no load on inputs/outputs, no 24 V supply via DRIVE-CLiQ and PROFIBUS interface
Making current, typ.	5 A
Power loss, typ.	17 W

Ambient temperature, during	-25 ... +55 °C
<ul style="list-style-type: none"> <li>• long-term storage</li> <li>• transport</li> <li>• operation</li> <li>— note</li> </ul>	-40 ... +70 °C 0 ... 55 °C
Relative humidity	Maximum installation altitude 4000 m (13124 ft) above sea level. Above an altitude of 2000 m (6562 ft), the maximum ambient temperature decreases by 7 °C (12.6 °F) per 1000 m (3281 ft).
<ul style="list-style-type: none"> <li>• during operation</li> <li>• without condensation, tested acc. to IEC 60068-2-38</li> </ul>	5 ... 95 % Wert fehlt
Product property / Conformal coating	No
Resistance	No
<ul style="list-style-type: none"> <li>• to biologically active substances, / conformity acc. to EN 60721-3-3</li> <li>• to chemically active substances, / conformity acc. to EN 60721-3-3</li> </ul>	No
Air pressure	620 ... 1 060 hPa
Degree of protection	IP20 / UL open type
height	380 mm
width	50 mm
<ul style="list-style-type: none"> <li>• depth</li> <li>• Depth / Note</li> </ul>	270 mm When the spacer is removed 230 mm (9.05 in) deep
net weight	3 700 g

#### Digital inputs / header

number of digital inputs	12
DC input voltage	24 V
<ul style="list-style-type: none"> <li>• rated value</li> <li>• for signal "1"</li> <li>• for signal "0"</li> </ul>	15 ... 30 V -3 ... +5 V
Electrical isolation	Yes
<ul style="list-style-type: none"> <li>• note</li> </ul>	Yes, in groups of 6
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	50 µs
<ul style="list-style-type: none"> <li>• signal "0" → "1", typ.</li> <li>• signal "1" → "0", typ.</li> </ul>	150 µs

#### Digital inputs/outputs / header

Number of digital I/Os	16
Parameterization possibility of the digital I/Os	can be parameterized - as DI - as DO - as probe input (max. 16) - as cam output (max. 8)

#### If used as an input / header

DC input voltage	24 V
<ul style="list-style-type: none"> <li>• rated value</li> <li>• for signal "1"</li> <li>• for signal "0"</li> </ul>	15 ... 30 V -3 ... +5 V
Electrical isolation	No
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	5 µs
<ul style="list-style-type: none"> <li>• signal "0" → "1", typ.</li> <li>• signal "1" → "0", typ.</li> </ul>	50 µs
Measuring input / reproducibility	5 µs
Measuring input / resolution	1 µs

#### If used as an output / header

Load voltage	24 V
<ul style="list-style-type: none"> <li>• rated value</li> <li>• minimum</li> <li>• maximum</li> </ul>	20.4 V 28.8 V
Electrical isolation	No
Current carrying capacity for each output, max.	500 mA
Leakage current, max.	2 mA
Output delay for	150 µs
<ul style="list-style-type: none"> <li>• signal "0" → "1", typ.</li> <li>• signal "0" → "1", max.</li> <li>• signal "1" → "0", typ.</li> </ul>	400 µs 75 µs

<ul style="list-style-type: none"> <li>• signal "1" → "0", max. — note</li> </ul>	150 μs Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut
Cam output	
<ul style="list-style-type: none"> <li>• reproducibility</li> <li>• resolution</li> </ul>	10 μs 1 μs
Switching frequency of the outputs for	
<ul style="list-style-type: none"> <li>• resistive load, max.</li> <li>• inductive load, max.</li> <li>• lamp load, max.</li> </ul>	4 kHz 2 Hz 11 Hz
Short-circuit protection	Yes
<b>Additional technical data</b>	
Back-up of non-volatile data	
<ul style="list-style-type: none"> <li>• of retentive data</li> <li>• of real-time clock, min.</li> <li>• note</li> </ul>	unlimited buffer duration 4 d longer buffer duration of the real-time clock using a battery inserted in the double fan/battery module
Charging time, typ.	
<ul style="list-style-type: none"> <li>• note</li> </ul>	A few minutes
Approvals	
<ul style="list-style-type: none"> <li>• USA</li> <li>• Canada</li> <li>• Australia</li> <li>• Korea</li> <li>• Russia, Belarus and Kazakhstan</li> </ul>	cULus cULus RCM (formerly C-Tick) KCC EAC

