



Circuit breaker size S0 for motor protection, CLASS 10 A-release 30...36 A  
N-release 432 A screw terminal Standard switching capacity

|                                 |                      |
|---------------------------------|----------------------|
| <b>product brand name</b>       | SIRIUS               |
| <b>product designation</b>      | Circuit breaker      |
| <b>design of the product</b>    | For motor protection |
| <b>product type designation</b> | 3RV2                 |

### General technical data

|   |                   |
|---|-------------------|
| <b>size of the circuit-breaker</b>                                | S0                |
| <b>size of contactor can be combined company-specific</b>         | S00, S0           |
| product extension auxiliary switch                                | Yes               |
| <b>power loss [W] for rated value of the current</b>              |                   |
| • at AC in hot operating state                                    | 16.25 W           |
| • at AC in hot operating state per pole                           | 5.4 W             |
| insulation voltage with degree of pollution 3 at AC rated value   | 690 V             |
| <b>surge voltage resistance rated value</b>                       | 6 kV              |
| <b>shock resistance according to IEC 60068-2-27</b>               | 25g / 11 ms       |
| <b>mechanical service life (operating cycles)</b>                 |                   |
| • of the main contacts typical                                    | 100 000           |
| • of auxiliary contacts typical                                   | 100 000           |
| electrical endurance (operating cycles) typical                   | 100 000           |
| <b>type of protection according to ATEX directive 2014/34/EU</b>  | Ex II (2) GD      |
| certificate of suitability according to ATEX directive 2014/34/EU | DMT 02 ATEX F 001 |
| <b>reference code according to IEC 81346-2</b>                    | Q                 |
| <b>Substance Prohibitance (Date)</b>                              | 10/01/2009        |

### Ambient conditions

|   |                |
|---|----------------|
| installation altitude at height above sea level maximum | 2 000 m        |
| <b>ambient temperature</b>                              |                |
| • during operation                                      | -20 ... +40 °C |
| • during storage  | -50 ... +80 °C |
| • during transport                                      | -50 ... +80 °C |
| relative humidity during operation                      | 10 ... 95 %    |

### Main circuit

|  |              |
|--|--------------|
| <b>number of poles for main current circuit</b>  | 3            |
| <b>adjustable current response value current of the current-dependent overload release</b> | 30 ... 36 A  |
| <b>operating voltage</b>   |              |
| • rated value  | 20 ... 690 V |
| • at AC-3 rated value maximum  | 690 V        |
| <b>operating frequency rated value</b>   | 50 ... 60 Hz |
| <b>operational current rated value</b>   | 36 A         |
| <b>operational current</b>   |              |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> </ul>  | 36 A   |
| <b>operating power</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>   | 7.5 kW<br>18.5 kW<br>22 kW<br>30 kW                                      |
| <b>operating frequency</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 maximum</li> </ul>   | 15 1/h   |
| <b>Auxiliary circuit</b>  |  |
| <b>number of NC contacts for auxiliary contacts</b>   | 0  |
| <b>number of NO contacts for auxiliary contacts</b>   | 0  |
| <b>number of CO contacts for auxiliary contacts</b>   | 0  |
| <b>Protective and monitoring functions</b>  |  |
| <b>product function</b>   |  |
| <ul style="list-style-type: none"> <li>• ground fault detection</li> <li>• phase failure detection</li> </ul>   | No<br>Yes  |
| <b>trip class</b>   | CLASS 10   |
| <b>design of the overload release</b>   | thermal  |
| <b>maximum short-circuit current breaking capacity (I<sub>cu</sub>)</b>   |  |
| <ul style="list-style-type: none"> <li>• at AC at 240 V rated value</li> <li>• at AC at 400 V rated value</li> <li>• at AC at 500 V rated value</li> <li>• at AC at 690 V rated value</li> </ul>  | 100 kA<br>20 kA<br>6 kA<br>3 kA  |
| <b>operating short-circuit current breaking capacity (I<sub>cs</sub>) at AC</b>   |  |
| <ul style="list-style-type: none"> <li>• at 240 V rated value</li> <li>• at 400 V rated value</li> <li>• at 500 V rated value</li> <li>• at 690 V rated value</li> </ul>  | 100 kA<br>10 kA<br>3 kA<br>2 kA  |
| response value current of instantaneous short-circuit trip unit   | 432 A  |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> <li>• at 600 V rated value</li> </ul>  | 36 A<br>36 A   |
| <b>yielded mechanical performance [hp]</b>  |  |
| <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> <li>— at 460/480 V rated value</li> </ul> </li> </ul> | 3 hp<br>5 hp<br>10 hp<br>10 hp<br>25 hp                                  |
| <b>Short-circuit protection</b>   |  |
| <b>product function short circuit protection</b>  | Yes  |
| <b>design of the short-circuit trip</b>   | magnetic   |
| <b>design of the fuse link for IT network for short-circuit protection of the main circuit</b>  |  |
| <ul style="list-style-type: none"> <li>• at 400 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul>  | gG 63 A<br>gG 63 A<br>gG 63 A  |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | any  |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715 |
| <b>height</b>   | 97 mm  |
| <b>width</b>  | 45 mm  |
| <b>depth</b>  | 97 mm  |
| <b>required spacing</b>   |  |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting at the side</li> <li>• for grounded parts at 400 V <ul style="list-style-type: none"> <li>— downwards</li> </ul> </li> </ul>  | 9 mm<br>30 mm  |

|                               |       |
|-------------------------------|-------|
| — upwards                     | 30 mm |
| — at the side                 | 9 mm  |
| • for live parts at 400 V     |       |
| — downwards                   | 30 mm |
| — upwards                     | 30 mm |
| — at the side                 | 9 mm  |
| • for grounded parts at 500 V |       |
| — downwards                   | 30 mm |
| — upwards                     | 30 mm |
| — at the side                 | 9 mm  |
| • for live parts at 500 V     |       |
| — downwards                   | 30 mm |
| — upwards                     | 30 mm |
| — at the side                 | 9 mm  |
| • for grounded parts at 690 V |       |
| — downwards                   | 70 mm |
| — upwards                     | 70 mm |
| — backwards                   | 0 mm  |
| — at the side                 | 30 mm |
| — forwards                    | 0 mm  |
| • for live parts at 690 V     |       |
| — downwards                   | 70 mm |
| — upwards                     | 70 mm |
| — backwards                   | 0 mm  |
| — at the side                 | 30 mm |
| — forwards                    | 0 mm  |

#### Connections/ Terminals

##### type of electrical connection

- for main current circuit

screw-type terminals

##### arrangement of electrical connectors for main current circuit

Top and bottom

##### type of connectable conductor cross-sections

- for main contacts
  - solid or stranded
  - finely stranded with core end processing
- at AWG cables for main contacts

2x (1 ... 2.5 mm<sup>2</sup>), 2x (2.5 ... 10 mm<sup>2</sup>)

2x (1 ... 2.5 mm<sup>2</sup>), 2x (2.5 ... 6 mm<sup>2</sup>), 1x 10 mm<sup>2</sup>

2x (16 ... 12), 2x (14 ... 8)

##### tightening torque

- for main contacts with screw-type terminals

2 ... 2.5 N·m

##### design of screwdriver shaft

Diameter 5 to 6 mm

##### size of the screwdriver tip

Pozidriv size 2

##### design of the thread of the connection screw

- for main contacts

M4

#### Safety related data

##### B10 value

- with high demand rate according to SN 31920

5 000

##### proportion of dangerous failures

- with low demand rate according to SN 31920
- with high demand rate according to SN 31920

50 %

50 %

##### failure rate [FIT]

- with low demand rate according to SN 31920

50 FIT

T1 value for proof test interval or service life according to IEC 61508

10 a

##### protection class IP on the front according to IEC 60529

IP20

##### touch protection on the front according to IEC 60529

display version for switching status

finger-safe, for vertical contact from the front

Handle

#### Certificates/ approvals

General Product Approval

For use in hazard-  
ous locations

[Confirmation](#)



[KC](#)



|                                |                           |                   |                   |
|--------------------------------|---------------------------|-------------------|-------------------|
| For use in hazardous locations | Declaration of Conformity | Test Certificates | Marine / Shipping |
|--------------------------------|---------------------------|-------------------|-------------------|



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Confirmation](#)

|       |         |
|-------|---------|
| other | Railway |
|-------|---------|



[Confirmation](#)

[Vibration and Shock](#)

**Further information**

**Siemens has decided to exit the Russian market (see here).**  
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**  
 Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2021-4PA10>

**Cax online generator**  
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2021-4PA10>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/3RV2021-4PA10>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2021-4PA10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2021-4PA10&lang=en)

**Characteristic: Tripping characteristics, I<sup>t</sup>, Let-through current**  
<https://support.industry.siemens.com/cs/ww/en/ps/3RV2021-4PA10/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**  
<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV2021-4PA10&objectype=14&gridview=view1>





last modified:

11/21/2022 