



Figure similar

SIMATIC S7-300, Analog input SM 331, Isolated 8 AI, resolution 13 bits  
U/I/resistor/Pt100, NI100, NI1000, LG-NI1000, PTC/KTY, 66 ms conversion  
time; 1x 40-pole

Input current	
from backplane bus 5 V DC, max.	90 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> <li>For resistance measurement</li> </ul>	8
permissible input voltage for voltage input (destruction limit), max.	30 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
<ul style="list-style-type: none"> <li>Voltage</li> <li>Current</li> <li>Thermocouple</li> <li>Resistance thermometer</li> <li>Resistance</li> </ul>	Yes Yes No Yes Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>0 to +10 V               <ul style="list-style-type: none"> <li>Input resistance (0 to 10 V)</li> </ul> </li> <li>1 V to 5 V               <ul style="list-style-type: none"> <li>Input resistance (1 V to 5 V)</li> </ul> </li> <li>1 V to 10 V</li> <li>-1 V to +1 V               <ul style="list-style-type: none"> <li>Input resistance (-1 V to +1 V)</li> </ul> </li> <li>-10 V to +10 V               <ul style="list-style-type: none"> <li>Input resistance (-10 V to +10 V)</li> </ul> </li> <li>-2.5 V to +2.5 V</li> <li>-250 mV to +250 mV</li> <li>-5 V to +5 V               <ul style="list-style-type: none"> <li>Input resistance (-5 V to +5 V)</li> </ul> </li> <li>-50 mV to +50 mV               <ul style="list-style-type: none"> <li>Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>-500 mV to +500 mV               <ul style="list-style-type: none"> <li>Input resistance (-500 mV to +500 mV)</li> </ul> </li> <li>-80 mV to +80 mV</li> </ul>	Yes 100 kΩ Yes 100 kΩ No Yes 100 kΩ Yes 100 kΩ No No Yes 100 kΩ Yes 100 kΩ Yes 100 kΩ No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>0 to 20 mA               <ul style="list-style-type: none"> <li>Input resistance (0 to 20 mA)</li> </ul> </li> <li>-10 mA to +10 mA</li> <li>-20 mA to +20 mA</li> </ul>	Yes 100 Ω No Yes

— Input resistance (-20 mA to +20 mA)	100 Ω
• -3.2 mA to +3.2 mA	No
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	100 Ω
<b>Input ranges (rated values), thermocouples</b>	
• Type B	No
• Type C	No
• Type E	No
• Type J	No
• Type K	No
• Type L	No
• Type N	No
• Type R	No
• Type S	No
• Type T	No
• Type U	No
• Type TXK/TXK(L) to GOST	No
<b>Input ranges (rated values), resistance thermometer</b>	
• Cu 10	No
• Ni 100	Yes; Standard/climate
— Input resistance (Ni 100)	100 MΩ
• Ni 1000	Yes
— Input resistance (Ni 1000)	100 MΩ
• LG-Ni 1000	Yes; Standard/climate
— Input resistance (LG-Ni 1000)	100 MΩ
• Ni 120	No
• Ni 200	No
• Ni 500	No
• Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	100 MΩ
• Pt 1000	No
• Pt 200	No
• Pt 500	No
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	No
• 0 to 300 ohms	No
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	100 MΩ
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	100 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	No
— internal temperature compensation	No
— external temperature compensation with compensations socket	No
<b>Characteristic linearization</b>	
• parameterizable	Yes
— for thermocouples	No
— for resistance thermometer	yes; Pt100 standard/air con.; Ni100 standard/air con.; Ni1000 standard/air con.; LG-Ni1000 standard/air con.
<b>Cable length</b>	
• shielded, max.	200 m; max. 50 m at 50 mV
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	13 bit
• Integration time, parameterizable	Yes; 60 / 50 ms
• Basic conversion time (ms)	66 / 55 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
• for voltage measurement	Yes
• for current measurement as 2-wire transducer	Yes; with external supply

<ul style="list-style-type: none"> <li>• for current measurement as 4-wire transducer</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with two-wire connection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with three-wire connection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with four-wire connection</li> </ul>	Yes
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.6 %; $\pm 0.6$ % ( $\pm 5$ V, 10 V, 1 to 5 V, 0 to 10 V); $\pm 0.5$ % ( $\pm 50$ mV, 500 mV, 1 V)
<ul style="list-style-type: none"> <li>• Current, relative to input range, (+/-)</li> </ul>	0.5 %; $\pm 20$ mA, 0 to 20 mA, 4 to 20 mA
<ul style="list-style-type: none"> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.5 %; 0 to 6 kohms, 0 to 600 kohms
<ul style="list-style-type: none"> <li>• Resistance thermometer, relative to input range, (+/-)</li> </ul>	1 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic); 1.2 Kelvin (Pt100, Ni100, standard)
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.4 %; 0.4% ( $\pm 5$ V, 10 V, 1 to 5 V, 0 to 10 V); 0.3% ( $\pm 50$ mV, 500 mV, 1 V)
<ul style="list-style-type: none"> <li>• Current, relative to input range, (+/-)</li> </ul>	0.3 %; $\pm 20$ mA, 0 to 20 mA, 4 to 20 mA
<ul style="list-style-type: none"> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.3 %; 0 to 6 kohms, 0 to 600 kohms
<ul style="list-style-type: none"> <li>• Resistance thermometer, relative to input range, (+/-)</li> </ul>	1 Kelvin (Pt100, Ni100, standard); 0.8 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic)
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
Alarms	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	No
<ul style="list-style-type: none"> <li>• Limit value alarm</li> </ul>	No
Diagnoses	
<ul style="list-style-type: none"> <li>• Diagnostic information readable</li> </ul>	No
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>• Group error SF (red)</li> </ul>	No
<b>Potential separation</b>	
Potential separation analog inputs	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>connection method / header</b>	
required front connector	40-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	117 mm
<b>Weights</b>	
Weight, approx.	250 g
<b>last modified:</b>	3/2/2021 