



SIMATIC DP, Connection ET 200M IM 153-2 High Feature for max. 12 S7-300 modules with redundancy capability, Timestamping suitable for isochronous mode New features: up to 12 modules can be used Slave INITIATIVE for Drive ES and Switch ES Expanded quantity structure for HART auxiliary variables Operation of the 64-channel modules 32 signals/slot +++Observe compatibility notes in manual+++

### General information

Product type designation	IM 153-2 DP HF
Firmware version	V6.0.0
Vendor identification (VendorID)	801Eh

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A

### Mains buffering

• Mains/voltage failure stored energy time	5 ms
--------------------------------------------	------

### Input current

Current consumption, max.	650 mA; with 24 V DC supply
Inrush current, typ.	3 A
I <sup>2</sup> t	0.1 A <sup>2</sup> ·s

### Output current

for backplane bus (5 V DC), max.	1.5 A
----------------------------------	-------

### Power loss

Power loss, typ.	5.5 W
------------------	-------

### Address area

Addressing volume	
• Inputs	244 byte
• Outputs	244 byte

### Hardware configuration

Number of modules per DP slave interface, max.	12
------------------------------------------------	----

### Time stamping

Accuracy	1 ms; 1 ms at up to 8 modules; 10 ms at up to 12 modules
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting

### Interfaces

Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s

### 1. Interface

automatic detection of transmission rate	Yes
Interface types	
• Output current of the interface, max.	70 mA
• Design of the connection	9-pin sub D socket
PROFIBUS DP slave	
• GSD file	SI05801E.GSG
• automatic baud rate search	Yes
<b>Protocols</b>	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
Protocols (Ethernet)	
• TCP/IP	No
PROFIBUS DP	
• Number of node addresses, max.	1 to 125 permitted
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes; as publisher with all IO, as subscriber with F-I/O only
<b>Potential separation</b>	
Potential separation exists	Yes
<b>Isolation</b>	
Isolation tested with	Isolation voltage 500 V
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m
<b>configuration / header</b>	
Configuration software	
• STEP 7	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	117 mm
<b>Weights</b>	
Weight, approx.	360 g
<b>last modified:</b>	4/1/2022 