



Insertion profile, for 95 mm<sup>2</sup> terminals, evens out the prismatic sleeve base when using flat conductors

Model		
product brand name	ALPHA	
product designation	Insertion profiles	
Appearance		
color	miscellaneous	
product feature insulated	Yes	
Mechanical Design		
fastening method	others	
net weight	7 g	
General Product Approval	Declaration of Conformity	other

[Confirmation](#)



EG-Konf.

[Confirmation](#)

[Miscellaneous](#)

### Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH9020-3NA00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8WH9020-3NA00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH9020-3NA00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9020-3NA00)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



