



Figure similar

SIMATIC DP, IM151-8 PN/DP CPU f. ET200S, 192 KB work memory, int. PROFINET interface (with three RJ45 ports) as IO controller, without battery MMC required

General information	
HW functional status	01
Firmware version	V3.2
Product function	
<ul style="list-style-type: none"> <li>• Isochronous mode</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>• Programming package</li> </ul>	as of STEP 7 V5.5 or as of STEP 7 TIA Portal V11
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; against destruction
external protection for power supply lines (recommendation)	2 A min.
Mains buffering	
<ul style="list-style-type: none"> <li>• Mains/voltage failure stored energy time</li> </ul>	5 ms
Input current	
Inrush current, typ.	1.8 A
$I^2t$	0.13 A <sup>2</sup> ·s
from supply voltage 1L+, max.	352 mA; 426 mA with DP master module
Output current	
for backplane bus (5 V DC), max.	700 mA
Power loss	
Power loss, typ.	5.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> <li>• integrated</li> </ul>	192 kbyte
<ul style="list-style-type: none"> <li>• expandable</li> </ul>	No
Load memory	
<ul style="list-style-type: none"> <li>• Plug-in (MMC)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Plug-in (MMC), max.</li> </ul>	8 Mbyte
<ul style="list-style-type: none"> <li>• Data management on MMC (after last programming), min.</li> </ul>	10 a
Backup	
<ul style="list-style-type: none"> <li>• present</li> </ul>	Yes; Ensured by SIMATIC Micro Memory Card (maintenance-free)
CPU processing times	
for bit operations, typ.	0.06 $\mu$ s
for word operations, typ.	0.12 $\mu$ s
for fixed point arithmetic, typ.	0.16 $\mu$ s
for floating point arithmetic, typ.	0.59 $\mu$ s

**CPU-blocks**

Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
--------------------------	---

**DB**

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Number, max.</li> <li>• Size, max.</li> </ul> | 1 024; Number range: 1 to 16000<br>64 kbyte |
|--|---|

**FB**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Number, max.</li> <li>• Size, max.</li> </ul> | 1 024; Number range: 0 to 7999<br>64 kbyte |
|--|--|

**FC**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Number, max.</li> <li>• Size, max.</li> </ul> | 1 024; Number range: 0 to 7999<br>64 kbyte |
|--|--|

**OB**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Number, max.</li> <li>• Size, max.</li> <li>• Number of free cycle OBs</li> <li>• Number of time alarm OBs</li> <li>• Number of delay alarm OBs</li> <li>• Number of cyclic interrupt OBs</li> <li>• Number of process alarm OBs</li> <li>• Number of DPV1 alarm OBs</li> <li>• Number of isochronous mode OBs</li> <li>• Number of startup OBs</li> <li>• Number of asynchronous error OBs</li> <li>• Number of synchronous error OBs</li> </ul> | See S7-300 operation list<br>64 kbyte<br>1; OB 1<br>1; OB 10<br>2; OB 20, 21<br>4; OB 32, 33, 34, 35<br>1; OB 40<br>3; OB 55, 56, 57<br>1; OB 61; only for PROFINET<br>1; OB 100<br>6; OB 80, 82, 83, 85, 86, 87 (OB83 only for centralized I/O and PROFINET IO)<br>2; OB 121, 122 |
|--|--|

**Nesting depth**

- |   |         |
|---|---------|
| <ul style="list-style-type: none"> <li>• per priority class</li> <li>• additional within an error OB</li> </ul> | 16<br>4 |
|---|---------|

**Counters, timers and their retentivity****S7 counter**

- |  |     |
|--|-----|
| <ul style="list-style-type: none"> <li>• Number</li> </ul> | 256 |
|--|-----|

**Retentivity**

- |               |            |
|---------------|------------|
| — adjustable  | Yes        |
| — lower limit | 0          |
| — upper limit | 255        |
| — preset      | Z 0 to Z 7 |

**Counting range**

- |               |     |
|---------------|-----|
| — adjustable  | Yes |
| — lower limit | 0   |
| — upper limit | 999 |

**IEC counter**

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• present</li> <li>• Type</li> <li>• Number</li> </ul> | Yes<br>SFB<br>Unlimited (limited only by RAM capacity) |
|---|--|

**S7 times**

- |  |     |
|--|-----|
| <ul style="list-style-type: none"> <li>• Number</li> </ul> | 256 |
|--|-----|

**Retentivity**

- |               |                |
|---------------|----------------|
| — adjustable  | Yes            |
| — lower limit | 0              |
| — upper limit | 255            |
| — preset      | No retentivity |

**Time range**

- |               |         |
|---------------|---------|
| — lower limit | 10 ms   |
| — upper limit | 9 990 s |

**IEC timer**

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• present</li> <li>• Type</li> <li>• Number</li> </ul> | Yes<br>SFB<br>Unlimited (limited only by RAM capacity) |
|---|--|

**Data areas and their retentivity**

Retentive data area (incl. timers, counters, flags), max.	64 kbyte
---	----------

**Flag**

- |   |                 |
|---|-----------------|
| <ul style="list-style-type: none"> <li>• Size, max.</li> <li>• Retentivity available</li> </ul> | 256 byte<br>Yes |
|---|-----------------|

<ul style="list-style-type: none"> <li>• Retentivity preset</li> <li>• Number of clock memories</li> </ul>	MB 0 to MB 15 8; 1 memory byte
<b>Data blocks</b>	
<ul style="list-style-type: none"> <li>• Retentivity adjustable</li> <li>• Retentivity preset</li> </ul>	Yes; via non-retain property on DB Yes
<b>Local data</b>	
<ul style="list-style-type: none"> <li>• per priority class, max.</li> </ul>	32 768 byte; Max. 2048 bytes per block
<b>Address area</b>	
<b>I/O address area</b>	
<ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>	2 048 byte 2 048 byte
of which distributed	
<ul style="list-style-type: none"> <li>— Inputs</li> <li>— Outputs</li> </ul>	2 048 byte 2 048 byte
<b>Process image</b>	
<ul style="list-style-type: none"> <li>• Inputs, adjustable</li> <li>• Outputs, adjustable</li> <li>• Inputs, default</li> <li>• Outputs, default</li> </ul>	2 048 byte 2 048 byte 128 byte 128 byte
<b>Subprocess images</b>	
<ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>	1; With PROFINET IO, the length of the user data is limited to 1600 bytes
<b>Digital channels</b>	
<ul style="list-style-type: none"> <li>• Inputs <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul>	16 336 496 16 336 496
<b>Analog channels</b>	
<ul style="list-style-type: none"> <li>• Inputs <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul>	1 021 124 1 021 124
<b>Hardware configuration</b>	
Number of modules per system, max.	63; Centralized
<b>Mounting rail</b>	
<ul style="list-style-type: none"> <li>• Number of mounting rails that can be used</li> <li>• Length of mounting rail, max.</li> </ul>	1 Station width: ≤ 1 m or < 2 m
<b>Time of day</b>	
<b>Clock</b>	
<ul style="list-style-type: none"> <li>• Hardware clock (real-time)</li> <li>• retentive and synchronizable</li> <li>• Backup time</li> <li>• Deviation per day, max.</li> <li>• Behavior of the clock following POWER-ON</li> <li>• Behavior of the clock following expiry of backup period</li> </ul>	Yes Yes 6 wk; At 40 °C ambient temperature, typically 10 s; Typ.: 2 s Clock continues running after POWER OFF the clock continues at the time of day it had when power was switched off
<b>Operating hours counter</b>	
<ul style="list-style-type: none"> <li>• Number</li> <li>• Number/Number range</li> <li>• Range of values</li> <li>• Granularity</li> <li>• retentive</li> </ul>	1 0 0 to 2 <sup>31</sup> hours (when using SFC 101) 1 h Yes; Must be restarted at each restart
<b>Clock synchronization</b>	
<ul style="list-style-type: none"> <li>• supported</li> <li>• to MPI, master</li> <li>• to MPI, slave</li> <li>• to DP, master</li> <li>• to DP, slave</li> <li>• in AS, master</li> <li>• in AS, slave</li> <li>• on Ethernet via NTP</li> </ul>	Yes No No Yes; With DP master module Yes; With DP master module No No Yes; As client
<b>Interfaces</b>	
Interfaces/bus type	1x PROFINET (3 RJ45 ports)

## 1. Interface

Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	Yes
<b>Interface types</b>	
<ul style="list-style-type: none"> <li>• RJ 45 (Ethernet)</li> <li>• Number of ports</li> <li>• integrated switch</li> </ul>	<p>Yes</p> <p>3; RJ45</p> <p>Yes</p>
<b>Protocols</b>	
<ul style="list-style-type: none"> <li>• MPI</li> <li>• PROFINET IO Controller</li> <li>• PROFINET IO Device</li> <li>• PROFINET CBA</li> <li>• PROFIBUS DP master</li> <li>• PROFIBUS DP slave</li> <li>• Open IE communication</li> <li>• Web server</li> <li>• Point-to-point connection</li> </ul>	<p>No</p> <p>Yes; Also simultaneously with IO-Device functionality</p> <p>Yes; Also simultaneously with IO Controller functionality</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes; Via TCP/IP, ISO on TCP, and UDP</p> <p>Yes</p> <p>No</p>
<b>PROFINET IO Controller</b>	
<ul style="list-style-type: none"> <li>• Transmission rate, max.</li> </ul>	100 Mbit/s; full duplex
<b>Services</b>	
<ul style="list-style-type: none"> <li>— PG/OP communication</li> <li>— Routing</li> <li>— S7 communication</li> <li>— Isochronous mode</li> <li>— IRT</li> <li>— Shared device</li> <li>— Prioritized startup</li> <li>— Number of IO devices with prioritized startup, max.</li> <li>— Number of connectable IO Devices, max.</li> <li>— Of which IO devices with IRT, max.</li> <li>— of which in line, max.</li> <li>— Number of IO Devices with IRT and the option "high flexibility"</li> <li>— of which in line, max.</li> <li>— Number of connectable IO Devices for RT, max.</li> <li>— of which in line, max.</li> <li>— Activation/deactivation of IO Devices</li> <li>— Number of IO Devices that can be simultaneously activated/deactivated, max.</li> <li>— IO Devices changing during operation (partner ports), supported</li> <li>— Number of IO Devices per tool, max.</li> <li>— Device replacement without swap medium</li> <li>— Send cycles</li> <li>— Updating time</li> <li>— Updating times</li> </ul>	<p>Yes</p> <p>Yes; With DP master module</p> <p>Yes; with loadable FBs</p> <p>Yes; OB 61; only for PROFINET IO</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>32</p> <p>128</p> <p>64</p> <p>64</p> <p>128</p> <p>61</p> <p>128</p> <p>128</p> <p>Yes</p> <p>8</p> <p>Yes</p> <p>8</p> <p>Yes</p> <p>250 <math>\mu</math>s, 500 <math>\mu</math>s, 1 ms; 2 ms, 4 ms (not in the case of IRT with "high flexibility" option)</p> <p>Minimum value depends on communication share set for PROFINET I/O, on the number of I/O devices, and on the number of configured user data items.</p> <p>250 <math>\mu</math>s to 512 ms (depends on operating mode; for more details, refer to Operating Instructions, "Interface Module IM151-8 PN/DP CPU")</p>
<b>Address area</b>	
<ul style="list-style-type: none"> <li>— Inputs, max.</li> <li>— Outputs, max.</li> <li>— User data consistency, max.</li> </ul>	<p>2 kbyte</p> <p>2 kbyte</p> <p>1 024 byte; with PROFINET I/O</p>
<b>PROFINET IO Device</b>	
<b>Services</b>	
<ul style="list-style-type: none"> <li>— PG/OP communication</li> <li>— Routing</li> <li>— S7 communication</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes; with loadable FBs</p>

— Isochronous mode	No
— IRT	Yes
— PROFINergy	Yes; With SFB 73 / 74 prepared for loadable PROFINergy standard FB for I-Device
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Transfer memory</b>	
— Inputs, max.	1 440 byte; Per IO Controller with shared device
— Outputs, max.	1 440 byte; Per IO Controller with shared device
<b>Submodules</b>	
— Number, max.	64
— User data per submodule, max.	1 024 byte
<b>PROFINET CBA</b>	
• acyclic transmission	Yes
• cyclic transmission	Yes
<b>Open IE communication</b>	
• Number of connections, max.	8
• Local port numbers used at the system end	0, 20, 21, 23, 25, 80, 102, 135, 161, 443, 8080, 34962, 34963, 34964, 65532, 65533, 65534, 65535
<b>2. Interface</b>	
Interface type	External interface via master module 6ES7138-4HA00-0AB0
Isolated	Yes
<b>Interface types</b>	
• RS 485	Yes
• Output current of the interface, max.	No
<b>Protocols</b>	
• MPI	No
• PROFINET IO Controller	No
• PROFINET IO Device	No
• PROFINET CBA	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
• Open IE communication	No
• Web server	No
<b>PROFIBUS DP master</b>	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32; Per station
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	No
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Number of DP slaves that can be simultaneously activated/deactivated, max.	8
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	2 048 byte
— Outputs, max.	2 048 byte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
<b>Protocols</b>	
<b>Redundancy mode</b>	
Media redundancy	

— MRP	Yes
— Switchover time on line break, typ.	200 ms; PROFINET MRP
— Number of stations in the ring, max.	50
<b>Open IE communication</b>	
• TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	8
— Data length for connection type 01H, max.	1 460 byte
— Data length for connection type 11H, max.	32 768 byte
— several passive connections per port, supported	Yes
• ISO-on-TCP (RFC1006)	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	8
— Data length, max.	32 768 byte
• UDP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	8
— Data length, max.	1 472 byte
<b>Web server</b>	
• supported	Yes
• User-defined websites	Yes
• Number of HTTP clients	5
<b>communication functions / header</b>	
PG/OP communication	Yes
Data record routing	Yes; With DP master module
<b>Global data communication</b>	
• supported	No
<b>S7 basic communication</b>	
• supported	Yes; I blocks
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes; via integrated PROFINET interface and loadable FBs
• User data per job, max.	See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication)
<b>communication functions / PROFINET CBA (with set target communication load) / header</b>	
• Setpoint for the CPU communication load	50 %
• number of remote connection partners / with PROFINET CBA	32
• number of technological functions / with PROFINET CBA / for master or slave	30
• number of connections / with PROFINET CBA / for master or slave / total	1 000
• data volume / of the input variables / with PROFINET CBA / for master or slave	4 000 byte
• data volume / of the output variables / with PROFINET CBA / for master or slave	4 000 byte
• number of internal and PROFIBUS interconnections / with PROFINET CBA / maximum	500
• data volume / of internal and PROFIBUS interconnections / with PROFINET CBA / for master or slave	4 000 byte
• data volume / with PROFINET CBA / per connection / maximum	1 400 byte
<b>performance data / PROFINET CBA / remote interconnection / with acyclic transfer / header</b>	
— update time / of the remote interconnections / in the case of acyclic transmission / with PROFINET CBA	500 ms
— number of remote connections to input variables / in the case of acyclic transmission / with PROFINET CBA / maximum	100
— number of remote connections to output variables / in the case of acyclic transmission / with PROFINET CBA / maximum	100
— data volume / as user data for remote interconnections with input variables / in the case of acyclic transmission / with PROFINET CBA	2 000 byte

— data volume / as user data for remote interconnections with output variables / in the case of acyclic transmission / with PROFINET CBA	2 000 byte
— data volume / as user data for remote interconnections / in the case of acyclic transmission / with PROFINET CBA / per connection / maximum	1 400 byte
<b>performance data / PROFINET CBA / remote interconnection / with cyclic transfer / header</b>	
— update time / of the remote interconnections / with cyclical transfer / with PROFINET CBA	1 ms
— number of remote connections to input variables / with PROFINET CBA / with cyclic transfer / maximum	200
— number of remote connections to output variables / with cyclical transfer / with PROFINET CBA / maximum	200
— data volume / as user data for remote interconnections with input variables / with cyclical transfer / with PROFINET CBA / maximum	2 000 byte
— data volume / as user data for remote interconnections with output variables / with cyclical transfer / with PROFINET CBA / maximum	2 000 byte
— data volume / as user data for remote interconnections / with cyclical transfer / with PROFINET CBA / per connection / maximum	450 byte
<b>performance data / PROFINET CBA / HMI variables via PROFINET / acyclic / header</b>	
— number of connectable HMI stations / for HMI variables / in the case of acyclic transmission / with PROFINET CBA	3; 2x PN OPC/1x iMap
— update time / of the HMI variables / in the case of acyclic transmission / with PROFINET CBA	500 ms
— number of HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	200
— data volume / as user data for HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	2 000 byte
<b>performance data / PROFINET CBA / PROFIBUS proxy functionality / header</b>	
— product function / with PROFINET CBA / PROFIBUS proxy functionality	Yes
— number of coupled PROFIBUS devices / with PROFIBUS functionality	16
— data volume / with PROFIBUS proxy functionality / with PROFINET CBA / per connection / maximum	240 byte; Slave-dependent
<b>iPAR server</b>	
• supported	Yes
<b>Number of connections</b>	
• overall	12
• usable for PG communication	11
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	11
• usable for OP communication	11
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	11
• usable for S7 basic communication	10
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	10
• usable for S7 communication	10; with loadable FBs
— adjustable for S7 communication, max.	10
• total number of instances, max.	32
• usable for routing	4; With DP master module
<b>S7 message functions</b>	
Number of login stations for message functions, max.	12; Depending on the configured connections for PG/OP and S7 basic communication

Process diagnostic messages simultaneously active Alarm-S blocks, max.	Yes; ALARM_S, ALARM_SC, ALARM_SQ, ALARM_D, ALARM_DQ 300
--	--

### Test commissioning functions

Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4

#### Status/control

- |                                    |   |
|------------------------------------|---|
| • Status/control variable          | Yes   |
| • Variables                        | Inputs, outputs, memory bits, DB, times, counters |
| • Number of variables, max.        | 30  |
| — of which status variables, max.  | 30  |
| — of which control variables, max. | 14  |

#### Forcing

- |                             |     |
|-----------------------------|-----|
| • Forcing                   | Yes |
| • Forcing, variables        | I/O |
| • Number of variables, max. | 10  |

#### Diagnostic buffer

- |                            |   |
|----------------------------|---|
| • present                  | Yes   |
| • Number of entries, max.  | 500   |
| — adjustable               | No  |
| — of which powerfail-proof | 100; Only the last 100 entries are retained |

### Interrupts/diagnostics/status information

Alarms	Yes
Diagnostics function	Yes

#### Diagnostics indication LED

- |   |                      |
|---|----------------------|
| • for maintenance                           | Yes; MT              |
| • Bus fault BF (red)                        | Yes; BF-PN           |
| • Group error SF (red)                      | Yes                  |
| • Monitoring 24 V voltage supply ON (green) | Yes                  |
| • Bus activity PROFINET (green)             | Yes; P1-/P2-/P3-Link |

### Potential separation

between PROFIBUS DP and all other circuit components	Yes
--	-----

### Isolation

Isolation tested with	500 V DC
-----------------------	----------

### Degree and class of protection

IP degree of protection	IP20
-------------------------	------

### configuration / header

#### Configuration software

- |          |                     |
|----------|---------------------|
| • STEP 7 | Yes; V5.5 or higher |
|----------|---------------------|

#### configuration / programming / header

- |                                |                      |
|--------------------------------|----------------------|
| • Command set                  | see instruction list |
| • Nesting levels               | 8                    |
| • System functions (SFC)       | see instruction list |
| • System function blocks (SFB) | see instruction list |

#### Programming language

- |            |               |
|------------|---------------|
| — LAD      | Yes           |
| — FBD      | Yes           |
| — STL      | Yes           |
| — SCL      | Yes; Optional |
| — CFC      | Yes; Optional |
| — GRAPH    | Yes; Optional |
| — HiGraph® | Yes; Optional |

#### Know-how protection

- |   |                            |
|---|----------------------------|
| • User program protection/password protection | Yes                        |
| • Block encryption                            | Yes; With S7 block Privacy |

#### programming / cycle time monitoring / header

- |                                  |          |
|----------------------------------|----------|
| • lower limit                    | 1 ms     |
| • upper limit                    | 6 000 ms |
| • adjustable                     | Yes      |
| • cycle monitoring time / preset | 150 ms   |

### Dimensions

Width	120 mm; DP master module: 35 mm
-------	---------------------------------



Height	119.5 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	320 g; DP master module: Approx. 100 g
<b>last modified:</b>	4/1/2022 