

Protistor[®] size 27x60 gLB 440VDC

SEMICONDUCTOR PROTECTION FUSES

IEC HIGH-SPEED CYLINDRICAL FUSE-LINKS DC PROTECTION



Mersen DC offers provide a very high performant protection for railway power and auxiliary circuits. Mersen DC Semiconductor fuse-links were developed to provide improved performance required by today's new DC equipment. These fuse-links are typically operated at more elevated temperature than other fuse type, have lower I^2t to minimize damage to protected components on short circuits, lower watts loss and longer life.

TECHNICAL DATA OVERVIEW

Voltage DC	440 VDC
Ampere Range (A)	125 ... 165 A
Speed/Characteristic	gLB
Product Size	27x60

FEATURES & BENEFITS

- Clearing all overloads
- Improved safety and protection
- Enabling selective coordination among all
- Distribution circuit fuses
- With trip-indicator

STANDARDS

- RoHS compliant



Protistor® size 27x60 gLB 440VDC


PRODUCT RANGE

Size 27x60 gLB 440VDC with striker

Catalog number	Item number	Rated voltage DC (IEC)	Rated current I_n	Rated breaking capacity DC	Rated breaking capacity DC @10ms	Rated breaking capacity DC @30ms	Power dissipation at 0.8 I_n	Power dissipation at I_n	Package	Weight
FD27GB44V125T	H098562	440 V	125 A	100 kA	100 kA	40 kA	12.6 W	22 W	10	80 g
FD27GB44V160T	M075704	440 V	160 A	100 kA	100 kA	40 kA	13.8 W	24.2 W	10	80 g

Protistor® size 27x60 gLB 440VDC


TIME CURRENT CHARACTERISTIC CURVES




MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.

Protistor® size 27x60 gLB 440VDC

L/R TIME CONSTANT VS DC VOLTAGE CAPABILITY



POWER DISSIPATION



Protistor® size 27x60 gLB 440VDC

DIMENSIONS

CP27x60 gLB 440V

